

INDUSTRIAL COMPONENT DATA

FAZ-C4/1-NA 102082 Y7-102082 EATON ELECTRIC Over current switch, 4A, 1p, C-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-C4/1-NA



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-C4/1-NA
Catalog number	Y7-102082
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-335CAEC9FE
Generated	2026-08-04

Product Overview

Over current switch, 4A, 1p, C-Char, AC

FAZ-C4/1-NA

Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB. FAZ-NA, 1-pole, tripping characteristic: C, rated current In: 4 A, Switchgear for export to North America (UL-listed)

Miniature circuit breaker (MCB), FAZ-NA, 1-pole, tripping characteristic: C, rated current In: 4 A, Switchgear for export to North America (UL-listed)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB Catalog Number 102082 Model Code FAZ-C4/1-NA
EAN 4015081019588 Product Length/Depth 105 mm Product Height 75.5 mm Product Width 17.7 mm Product Weight
0.122 kg Compliances RoHS conform Certifications CSA-C22.2 No. 5-09

IEC 60947-2

IEC/EN 60947-2

CSA (Class No. 1432-01)

UL 489, CSA C22.2 No. 5

Specially designed for North America, suitable as BCPD

CSA (File No. 204453)

UL (File No. E235139)

UL (Category Control Number DIVQ)

UL 489

North America (UL listed, CSA certified)

CE marking

EN45545-2

IEC 61373 Catalog Notes Positioned for medium inrush startup currents to provide protection for small transformers and pilot devices. Delivery program

Application Number of poles Single-pole Number of poles (total) 1 Number of poles (protected) 1 Tripping characteristic C

Release characteristic C Amperage Rating 4 A Type FAZ-NA

Miniature circuit breaker

Technical data - electrical

Voltage type AC Voltage rating 277 V AC / 480 V AC Voltage rating at DC 60 V DC Voltage rating (IEC/EN 60947-2) 254 V

Voltage rating (UL) 277 V Rated operational voltage (Ue) - max 240 V Rated insulation voltage (Ui) 440 V Rated impulse

withstand voltage (Uimp) 4 kV Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated switching capacity

(IEC/EN 60947-2) 15 kA Breaking capacity 10 kA (UL489) Rated short-circuit breaking capacity (EN 60898) at 230 V 0 kA

Rated short-circuit breaking capacity (EN 60898) at 400 V 0 kA Ra...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-C4/1-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.