


INDUSTRIAL COMPONENT DATA

FAZ-D50/2 115372 Y7-115372 EATON ELECTRIC Over current switch, 50A, 2p, type D characteristic

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-D50/2



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-D50/2
Catalog number	Y7-115372
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-FD19107AF7
Generated	2026-08-02

Product Overview

Over current switch, 50A, 2p, type D characteristic

FAZ-D50/2

Eaton Moeller series xEffect - FAZ MCB. Miniature circuit breaker (MCB), 50 A, 2p, characteristic: D

High-quality miniature circuit breaker for industrial applications and residential applications, contact position indicator red - green, guide for secure terminal connection, tri-stable slide catch - enables removal from existing busbar system, comprehensive range of accessories suitable for subsequent installation, rated currents up to 63 A, tripping characteristics B, C, D

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ MCB Catalog Number 115372 Model Code FAZ-D50/2 EAN

4015081147724 Product Length/Depth 80 mm Product Height 75.5 mm Product Width 36 mm Product Weight 0.245 kg

Compliances UL CSA09 (with supplementary protector only)

RoHS conform Certifications North America (UL recognized, CSA certified)

CSA (File No. 204453)

UL (Category Control Number QVNU2, QVNU8)

UL (File No. E177451)

IEC/EN 60898

IEC/EN 60947-2

UL 1077

CSA (Class No. 3215-30)

CE marking

CSA-C22.2 No. 235

EN45545-2

IEC 61373 Delivery Programme

Application Number of poles Two-pole Number of poles (total) 2 Number of poles (protected) 2 Tripping characteristic D

Release characteristic D Amperage Rating 50 A Type FAZ

Miniature circuit breaker

Technical data - electrical

Voltage type AC Voltage rating 240 V AC / 415 V AC Voltage rating (UL CSA 13) 480 Y/277 V AC; 96 V DC Rated

operational voltage (Ue) - max 400 V Rated insulation voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV

Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated switching capacity (IEC/EN 60947-2) 10 kA Rated

short-circuit breaking capacity (EN 60898) at 230 V 10 kA Rated short-circuit breaking capacity (EN 60898) at 400 V 10 kA

Rated short-circuit breaking capacity (IEC 60947-2) at 230 V 10 kA Rated short-circuit breaking capacity (IEC 60947-2) at

400 V 10 kA Overvoltage category III Pollution degree 2 Technical data - mechanical

Width in number of modular spaci...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-D50/2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.