

INDUSTRIAL COMPONENT DATA

FAZ-D0,5/3-NA 102257 Y7-102257 EATON ELECTRIC Over current switch, 0,5A, 3p, D-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-D0,5/3-NA



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-D0,5/3-NA
Catalog number	Y7-102257
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-7B9DC8CBB4
Generated	2026-08-03

Product Overview

Over current switch, 0,5A, 3p, D-Char, AC

FAZ-D0,5/3-NA

Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB. FAZ-NA, 3-pole, tripping characteristic: D, rated current In: 0.5 A, Switchgear for export to North America (UL-listed)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB Catalog Number 102257 Model Code FAZ-D0,5/3-NA
EAN 4015081021338 Product Length/Depth 105 mm Product Height 75.5 mm Product Width 53.1 mm Product Weight
0.363 kg Compliances RoHS conform Certifications IEC 60947-2

CSA (Class No. 1432-01)

UL (File No. E235139)

North America (UL listed, CSA certified)

UL 489, CSA C22.2 No. 5

CSA (File No. 204453)

CE marking

CSA-C22.2 No. 5-09

UL (Category Control Number DIVQ)

Specially designed for North America, suitable as BCPD

IEC/EN 60947-2

UL 489

EN45545-2

IEC 61373 Product specifications

Type Special features Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity Application Feeder circuits, branch circuits

Switchgear for export to North America (UL-listed)

Amperage Rating 0.5 A Voltage rating 277 V AC / 480 V AC Features Additional equipment possible Frame 45 mm

Pollution degree 2 Used with Miniature circuit breaker

FAZ-NA Mounting Method Top-hat rail IEC/EN 60715 Degree of protection IP20

UL/CSA Type: -

IP20 (IEC)

IP40 (when fitted) Equipment heat dissipation, current-dependent 3.5 W Rated impulse withstand voltage (Uimp) 4 kV

Terminal protection Finger and hand touch safe, DGUV VS3, EN 50274 Terminals (top and bottom) Twin-purpose terminals

Tripping characteristic D Ambient operating temperature - max 75 °C Ambient operating temperature - min -25 °C Built-in

depth 70.5 mm Connectable conductor cross....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-D0,5/3-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.