

## INDUSTRIAL COMPONENT DATA

# PLSM-C63/3N-MW 242549 Y7-242549 EATON ELECTRIC Over current switch, 63A, 3pole+N, type C characteristic

Brand: EATON - MOELLER | Manufacturer Part Number: PLSM-C63/3N-MW



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | EATON - MOELLER                 |
| MPN / Reference | PLSM-C63/3N-MW                  |
| Catalog number  | Y7-242549                       |
| Category        | Miniature circuit breaker (MCB) |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-B4076D4BB0                   |
| Generated       | 2026-08-04                      |

## Product Overview

Over current switch, 63A, 3pole+N, type C characteristic

PLSM-C63/3N-MW

Eaton Moeller series xPole - PLS6/M MCB. PLSM, 3-pole+N, tripping characteristic: C, rated current In: 63 A, rated switching capacity IEC/EN 60898-1: 10 kA

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

## Additional Product Information

### General specifications

Product Name Eaton Moeller series xPole - PLS6/M MCB Catalog Number 242549 Model Code PLSM-C63/3N-MW EAN 4015082425494 Product Length/Depth 80 mm Product Height 75 mm Product Width 70 mm Product Weight 0.474 kg

Compliances RoHS conform Delivery program

Application Number of poles Three-pole + N Number of poles (total) 4 Number of poles (protected) 3 Tripping characteristic C Release characteristic C Amperage Rating 63 A Type Miniature circuit breaker

PLSM

### Technical data - electrical

Voltage type AC Rated operational voltage (Ue) - max 400 V Rated insulation voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated switching capacity (IEC/EN 60898-1) 10 kA Rated short-circuit breaking capacity (EN 60898) at 230 V 10 kA Rated short-circuit breaking capacity (EN 60898) at 400 V 10 kA Rated short-circuit breaking capacity (IEC 60947-2) at 230 V 0 kA Rated short-circuit breaking

capacity (IEC 60947-2) at 400 V 0 kA Overvoltage category III Pollution degree 2 Technical data - mechanical  
Width in number of modular spacings 4 Built-in depth 70.5 mm Degree of protection IP20 Connectable conductor cross  
section (solid-core) - min 1 mm<sup>2</sup> Connectable conductor cross section (solid-core) - max 25 mm<sup>2</sup> Connectable conductor  
cross section (multi-wired) - min 1 mm<sup>2</sup> Connectable conductor cross section (multi-wired) - max 25 mm<sup>2</sup> Design verification  
as per IEC/EN 61439 - technical data  
Rated operational c...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PLSM-C63/3N-MW with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.