

INDUSTRIAL COMPONENT DATA

FAZ-C7/2-NA 102165 Y7-102165 EATON ELECTRIC Miniature circuit breaker (MCB), 7A, 2p, C-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-C7/2-NA



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-C7/2-NA
Catalog number	Y7-102165
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-A835BCDC34
Generated	2026-08-03

Product Overview

Miniature circuit breaker (MCB), 7A, 2p, C-Char, AC

FAZ-C7/2-NA

Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB. FAZ-NA, 2-pole, tripping characteristic: C, rated current In: 7 A, Switchgear for export to North America (UL-listed)

Miniature circuit breaker (MCB), FAZ-NA, 2-pole, tripping characteristic: C, rated current In: 7 A, Switchgear for export to North America (UL-listed)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB Catalog Number 102165 Model Code FAZ-C7/2-NA
EAN 4015081020416 Product Length/Depth 105 mm Product Height 75.5 mm Product Width 35.4 mm Product Weight
0.243 kg Compliances RoHS conform Certifications CSA-C22.2 No. 5-09

IEC/EN 60947-2

UL 489

UL (Category Control Number DIVQ)

UL (File No. E235139)

Specially designed for North America, suitable as BCPD

CSA (File No. 204453)

North America (UL listed, CSA certified)

CSA (Class No. 1432-01)

IEC 60947-2

CE marking

UL 489, CSA C22.2 No. 5

EN45545-2

IEC 61373 Delivery program

Application Number of poles Two-pole Number of poles (total) 2 Number of poles (protected) 2 Tripping characteristic C

Release characteristic C Amperage Rating 7 A Type FAZ-NA

Miniature circuit breaker

Technical data - electrical

Voltage type AC Voltage rating 277 V AC / 480 V AC Voltage rating at DC 60 V DC Voltage rating (IEC/EN 60947-2) 440 V

Voltage rating (UL) 480Y/277 V Rated operational voltage (Ue) - max 415 V Rated insulation voltage (Ui) 440 V Rated

impulse withstand voltage (Uimp) 4 kV Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated switching

capacity (IEC/EN 60947-2) 15 kA Breaking capacity 10 kA (UL489) Rated short-circuit breaking capacity (EN 60898) at 230

V 0 kA Rated short-circuit breaking capacity (EN 60898) at 400 V 0 kA Rated short-circuit breaking capacity (IEC 60947-2)

at 230 V 15 kA Rated short-circuit breaking capacity (IEC 60947-2) at 40...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-C7/2-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.