

INDUSTRIAL COMPONENT DATA

ZB12-0,16 278431 XTOBP16BC1 EATON ELECTRIC Overload relay, 0.1 0.16 A, 1N/O+1N/C

Brand: EATON - MOELLER | Manufacturer Part Number: ZB12-0,16



Manufacturer	EATON - MOELLER
MPN / Reference	ZB12-0,16
Catalog number	Y7-278431
Category	Thermal overload relay
Minimum order	1 Pcs
Document ID	EO-ACC41EB881
Generated	2026-08-04

Product Overview

Overload relay, 0.1 - 0.16 A, 1N/O+1N/C

ZB12-0,16

Overload relay, ZB12, Ir= 0.1 - 0.16 A, 1 N/O, 1 N/C, Direct mounting, IP20

Overload relay, Product range: Overload relay ZB up to 150 A, Accessories: Overload relays, Frame size: ZB12, Phase-failure sensitivity: IEC/EN 60947, VDE 0660 Part 102, Description: Test/off button, Reset pushbutton manual/auto, Trip-free release, Mounting type: Direct mounting, Auxiliary contacts N/O = Normally open: 1 N/O, Auxiliary contacts N/C = Normally closed: 1 N/C, For use with: DILM7, DILM9, DILM12, DILM15,, DIULM7, DIULM9, DIULM12,, SDAINLM12,, SDAINLM16,, SDAINLM22, Standards: IEC/EN 60947, VDE 0660, UL, CSA, Degree of Protection: IP20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Thermal Relays

Additional Product Information

EL-Nummer (Norway)4131826Overload relay, ZB12, Ir= 0.1 - 0.16 A, 1 N/O, 1 N/C, Direct mounting, IP20Overload relay, Product range: Overload relay ZB up to 150 A, Accessories: Overload relays, Frame size: ZB12, Phase-failure sensitivity: IEC/EN 60947, VDE 0660 Part 102, Description: Test/off button, Reset pushbutton manual/auto, Trip-free release, Mounting type: Direct mounting, Auxiliary contacts N/O = Normally open: 1 N/O, Auxiliary contacts N/C = Normally closed: 1 N/C, For use with: DILM7, DILM9, DILM12, DILM15,, DIULM7, DIULM9, DIULM12,, SDAINLM12,, SDAINLM16,, SDAINLM22, Standards: IEC/EN 60947, VDE 0660, UL, CSA, Degree of Protection: IP20Delivery program Product rangeOverload relay ZB up to 150 AProduct rangeAccessoriesAccessoriesOverload relaysFrame sizeZB12Phase-failure sensitivityIEC/EN 60947, VDE 0660 Part 102DescriptionTest/off button

Reset pushbutton manual/auto

Trip-free releaseMounting typeDirect mounting[Ir]0.1 - 0.16 AContact sequenceAuxiliary contactsN/O = Normally open1

N/ON/C = Normally closed1 N/CFor use withDILM7, DILM9, DILM12, DILM15,

DIULM7, DIULM9, DIULM12,

SDAINLM12,

SDAINLM16,

SDAINLM22Short-circuit protectionType "1" coordination[gG/gL]25 AType "2" coordination[gG/gL]0.5 ANotesOverload

release: tripping class 10 A

short-circuit protective device: Observe the maximum permissible fuse of the contactor with direct device mounting.

Suitable for protection of Ex e-motors.

II(2)G [Ex d] [Ex e] [Ex px], II(2)D [Ex p] [Ex t]

PTB 10 ATEX 3010

Observe manu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ZB12-0,16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.