

INDUSTRIAL COMPONENT DATA

ZB32-0,4 278444 Y7-278444 EATON ELECTRIC Overload relay, 0.24-0.4A, 1N/O+1N/C

Brand: EATON - MOELLER | Manufacturer Part Number: ZB32-0,4



Manufacturer	EATON - MOELLER
MPN / Reference	ZB32-0,4
Catalog number	Y7-278444
Category	Thermal overload relay
Minimum order	1 Pcs
Document ID	EO-2323BA7AE7
Generated	2026-08-04

Product Overview

Overload relay, 0.24-0.4A, 1N/O+1N/C

ZB32-0,4

Overload relay, ZB32, Ir= 0.24 - 0.4 A, 1 N/O, 1 N/C, Direct mounting, IP20

Overload relay, Product range: Overload relay ZB up to 150 A, Accessories: Overload relays, Frame size: ZB32, Phase-failure sensitivity: IEC/EN 60947, VDE 0660 Part 102, Description: Test/off button, Reset pushbutton manual/auto, Trip-free release, Mounting type: Direct mounting, Auxiliary contacts N/O = Normally open: 1 N/O, Auxiliary contacts N/C = Normally closed: 1 N/C, For use with: DILM17, DILM25,, DILM32,, DILM38,, DILMF8,, DILMF11,, DILMF14,, DILMF17,, DILMF25,, DILMF32,, DIULM17, DIULM25,, DIULM32,, SDAINLM30,, SDAINLM45,, SDAINLM55, Standards: IEC/EN 60947, VDE 0660, UL, CSA, Degree of Protection: IP20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Thermal Relays

Additional Product Information

EL-Nummer (Norway)4131839Overload relay, ZB32, Ir= 0.24 - 0.4 A, 1 N/O, 1 N/C, Direct mounting, IP20Overload relay, Product range: Overload relay ZB up to 150 A, Accessories: Overload relays, Frame size: ZB32, Phase-failure sensitivity: IEC/EN 60947, VDE 0660 Part 102, Description: Test/off button, Reset pushbutton manual/auto, Trip-free release, Mounting type: Direct mounting, Auxiliary contacts N/O = Normally open: 1 N/O, Auxiliary contacts N/C = Normally closed: 1 N/C, For use with: DILM17, DILM25,, DILM32,, DILM38,, DILMF8,, DILMF11,, DILMF14,, DILMF17,, DILMF25,, DILMF32,, DIULM17, DIULM25,, DIULM32,, SDAINLM30,, SDAINLM45,, SDAINLM55, Standards: IEC/EN 60947, VDE 0660, UL, CSA, Degree of Protection: IP20Delivery program

Product range Overload relay ZB up to 150 A Product range Accessories Accessories Overload relays Frame size ZB32 Phase-failure sensitivity IEC/EN 60947, VDE 0660 Part 102 Description Test/off button Reset pushbutton manual/auto Trip-free release Mounting type Direct mounting [I_r] 0.24 - 0.4 A Contact sequence Auxiliary contacts N/O = Normally open 1 N/ON/C = Normally closed 1 N/C For use with DILM17, DILM25, DILM32, DILM38, DILMF8, DILMF11, DILMF14, DILMF17, DILMF25, DILMF32, DIULM17, DIULM25, DIULM32, SDAINLM30, SDAINLM45, SDAINLM55 Short-circuit protection Type "1" coordination [gG/gL] 25 A Type "2" coordination [gG/gL] 2 A Notes Overload release: tripping class 10 A short-circuit protective device: Observe the maximum permissible fuse of the contactor with direct device mounting....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ZB32-0,4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.