

INDUSTRIAL COMPONENT DATA

ZB150-150 278466 Y7-278466 EATON ELECTRIC Overload relay, 120-142A, 1N/O+1N/C

Brand: EATON - MOELLER | Manufacturer Part Number: ZB150-150



Manufacturer	EATON - MOELLER
MPN / Reference	ZB150-150
Catalog number	Y7-278466
Category	Thermal overload relay
Minimum order	1 Pcs
Document ID	EO-144587D276
Generated	2026-08-05

Product Overview

Overload relay, 120-142A, 1N/O+1N/C

ZB150-150

Overload relay, ZB150, Ir= 120 - 150 A, 1 N/O, 1 N/C, Direct mounting, IP00

Overload relay, Product range: Overload relay ZB up to 150 A, Accessories: Overload relays, Frame size: ZB150, Phase-failure sensitivity: IEC/EN 60947, VDE 0660 Part 102, Description: Test/off button, Reset pushbutton manual/auto, Trip-free release, Mounting type: Direct mounting, Auxiliary contacts N/O = Normally open: 1 N/O, Auxiliary contacts N/C = Normally closed: 1 N/C, For use with: DILM80, DILM95, DILM115, DILM150, DILM170, DILMF80, DILMF95, DILMF115, DILMF150, DIULM80, DIULM95, DIULM115, DIULM150, SDAINLM140, SDAINLM165, SDAINLM200, SDAINLM260, Standards: IEC/EN 60947, VDE 0660, UL, CSA, Degree of Protection: IP00

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Thermal Relays

Additional Product Information

EL-Nummer (Norway)4134236Overload relay, ZB150, Ir= 120 - 150 A, 1 N/O, 1 N/C, Direct mounting, IP00Overload relay, Product range: Overload relay ZB up to 150 A, Accessories: Overload relays, Frame size: ZB150, Phase-failure sensitivity: IEC/EN 60947, VDE 0660 Part 102, Description: Test/off button, Reset pushbutton manual/auto, Trip-free release, Mounting type: Direct mounting, Auxiliary contacts N/O = Normally open: 1 N/O, Auxiliary contacts N/C = Normally closed: 1 N/C, For use with: DILM80, DILM95, DILM115, DILM150, DILM170, DILMF80, DILMF95, DILMF115, DILMF150, DIULM80, DIULM95, DIULM115, DIULM150, SDAINLM140, SDAINLM165, SDAINLM200, SDAINLM260, Standards: IEC/EN 60947, VDE 0660, UL, CSA, Degree of Protection: IP00Delivery program

Product range Overload relay ZB up to 150 A Product range Accessories Accessories Overload relays Frame size ZB150 Phase-failure sensitivity IEC/EN 60947, VDE 0660 Part 102 Description Test/off button Reset pushbutton manual/auto Trip-free release Mounting type Direct mounting [I_r] 120 - 150 A Contact sequence Auxiliary contacts N/O = Normally open 1 N/ON/C = Normally closed 1 N/C For use with DILM80 DILM95 DILM115 DILM150 DILM170 DILMF80 DILMF95 DILMF115 DILMF150 DIULM80 DIULM95 DIULM115 DIULM150 SDAINLM140 SDAINLM165 SDAINLM200 SDAINLM260 Short-circuit protection Type "1" coordination [gG/gL] 315 A Type "2" coordination [gG/gL] 250 A Notes Overload trigger: tripping class 10 A Short circuit protection: observe the maximum permissible fuse of the contactor with direct devi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ZB150-150 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.