


INDUSTRIAL COMPONENT DATA

ZB150-50/KK 278468 Y7-278468 EATON ELECTRIC Overload relay, 35-50A, 1N/O+1N/C

Brand: EATON - MOELLER | Manufacturer Part Number: ZB150-50/KK



Manufacturer	EATON - MOELLER
MPN / Reference	ZB150-50/KK
Catalog number	Y7-278468
Category	Thermal overload relay
Minimum order	1 Pcs
Document ID	EO-2330B5F474
Generated	2026-08-05

Product Overview

Overload relay, 35-50A, 1N/O+1N/C

ZB150-50/KK

Overload relay, ZB150, Ir= 35 - 50 A, 1 N/O, 1 N/C, Separate mounting, IP00

Overload relay, Product range: Overload relay ZB up to 150 A, Accessories: Overload relays, Frame size: ZB150, Phase-failure sensitivity: IEC/EN 60947, VDE 0660 Part 102, Description: Test/off button, Reset pushbutton manual/auto, Trip-free release, Mounting type: Separate mounting, Auxiliary contacts N/O = Normally open: 1 N/O, Auxiliary contacts N/C = Normally closed: 1 N/C, For use with: DILM80, DILM95, DILM115, DILM150, DILM170, DILMF80, DILMF95, DILMF115, DILMF150, DIULM80, DIULM95, DIULM115, DIULM150, SDAINLM140, SDAINLM165, SDAINLM200, SDAINLM260, Standards: IEC/EN 60947, VDE 0660, UL, CSA, Degree of Protection: IP00

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Thermal Relays

Additional Product Information

Overload relay, ZB150, Ir= 35 - 50 A, 1 N/O, 1 N/C, Separate mounting, IP00Overload relay, Product range: Overload relay ZB up to 150 A, Accessories: Overload relays, Frame size: ZB150, Phase-failure sensitivity: IEC/EN 60947, VDE 0660 Part 102, Description: Test/off button, Reset pushbutton manual/auto, Trip-free release, Mounting type: Separate mounting, Auxiliary contacts N/O = Normally open: 1 N/O, Auxiliary contacts N/C = Normally closed: 1 N/C, For use with: DILM80, DILM95, DILM115, DILM150, DILM170, DILMF80, DILMF95, DILMF115, DILMF150, DIULM80, DIULM95, DIULM115, DIULM150, SDAINLM140, SDAINLM165, SDAINLM200, SDAINLM260, Standards: IEC/EN 60947, VDE 0660, UL, CSA, Degree of Protection: IP00Delivery program

Product rangeOverload relay ZB up to 150 AProduct rangeAccessoriesAccessoriesOverload relaysFrame
sizeZB150Phase-failure sensitivityIEC/EN 60947, VDE 0660 Part 102DescriptionTest/off button
Reset pushbutton manual/auto
Trip-free releaseMounting typeSeparate mounting[Ir]35 - 50 AContact sequenceAuxiliary contactsN/O = Normally open1
N/ON/C = Normally closed1 N/CFor use withDILM80
DILM95
DILM115
DILM150
DILM170
DILMF80
DILMF95
DILMF115
DILMF150
DIULM80
DIULM95
DIULM115
DIULM150
SDAINLM140
SDAINLM165
SDAINLM200
SDAINLM260Short-circuit protectionType "1" coordination[gG/gL]160 AType "2" coordination[gG/gL]125 ANotesOverload
trigger: tripping class 10 A
Short circuit protection: observe the maximum permissible fuse of the contactor with direct device mounting.
Suitable f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ZB150-50/KK with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.