

INDUSTRIAL COMPONENT DATA

ZEB32-5-GF/KK 136499 Y7-136499 EATON ELECTRIC

Overload relay, electronic, 1-5A, separate mounting, +earth-fa..

Brand: EATON - MOELLER | Manufacturer Part Number: ZEB32-5-GF/KK



Manufacturer	EATON - MOELLER
MPN / Reference	ZEB32-5-GF/KK
Catalog number	Y7-136499
Category	Electronic overload relay
Minimum order	1 Pcs
Document ID	EO-82611D3557
Generated	2026-08-06

Product Overview

Overload relay, electronic, 1-5A, separate mounting, +earth-fault protection

ZEB32-5-GF/KK

Eaton Moeller® series ZEB Overload relay, Separate mounting, Earth-fault protection: with, Ir= 1 - 5 A, 1 N/O, 1 N/C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Electronic Circuit Breakers
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series ZEB Electronic overload relay Catalog Number 136499 Model Code ZEB32-5-GF/KK
EAN 4015081332793 Product Length/Depth 108 mm Product Height 110 mm Product Width 45 mm Product Weight 0.345
kg Certifications CSA File No.: 2290956

UL

CSA Class No.: 3211-03

CSA-C22.2 No. 14

IEC/EN 60947

UL 508

CE

UL Category Control No.: NKCR

CSA

IEC/EN 60947-4-1

VDE 0660

UL File No.: E1230 Catalog Notes Rated operational current: Switch-on and switch-off conditions based on DC-13, time constant as specified. Features & Functions

Earth fault protection Trip at approx. $> 0.5 \times I_r$ in 2 s

Trip at approx. $> 1.5 \times I_r$ in 1 s

Yes Features Phase-failure sensitivity (according to IEC/EN 60947, VDE 0660 Part 102) Functions Filament bulb (24 V)

General

Class Adjustable Degree of protection IP20 Mounting method Separate positioning

Separate mounting Overload release current setting - min 1 A Overload release current setting - max 5 A Overvoltage category III Pollution degree 3 Product Category Electronic overload relays ZEB Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC 6000 V (auxiliary circuits) Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Shock duration 10 ms Mechanical, According to IEC/EN 60068-2-27 Suitable for Branch circuits, (UL/CSA) Voltage type Self powered Climatic environmental conditions

Ambient operating...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ZEB32-5-GF/KK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.