

INDUSTRIAL COMPONENT DATA

P1-25/I2/HI11-NA 237540 Y7-237540 EATON ELECTRIC On-Off switch, 3 pole + 1 N/O + 1 N/C, 25 A, surface mounti..

Brand: EATON - MOELLER | Manufacturer Part Number: P1-25/I2/HI11-NA



Manufacturer	EATON - MOELLER
MPN / Reference	P1-25/I2/HI11-NA
Catalog number	Y7-237540
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-BB4A5C4880
Generated	2026-08-05

Product Overview

On-Off switch, 3 pole + 1 N/O + 1 N/C, 25 A, surface mounting, UL/CSA

P1-25/I2/HI11-NA

Eaton Moeller® series P1 On-Off switch, P1, 25 A, surface mounting, 3 pole, 1 N/O, 1 N/C, with black thumb grip and front plate, UL/CSA

On-Off switch, P1, Rated uninterrupted current (Iu): 25 A, Fitted with: Black thumb grip and front plate, Mounting method: Surface mounting, Number of poles: Three-pole, Degree of Protection: NEMA 12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 On-off switch Catalog Number 237540 Model Code P1-25/I2/HI11-NA EAN 4015082375409 Product Length/Depth 107 mm Product Height 180 mm Product Width 100 mm Product Weight 0.47 kg

Certifications CSA-C22.2 No. 94

IEC/EN 60947-3

UL File No.: E36332

CSA

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60204

CSA Class No.: 3211-05

UL
CE
CSA File No.: 012528
IEC/EN 60947
UL Category Control No.: NLRV
VDE 0660
UL 60947-4-1
ETIM for 237540 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as main switch (EF006981)
No
Version as maintenance-/service switch (EF006986)
No
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
No
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Max. rated operation voltage U_e AC (EF007355)
690 V
Rated operating voltage (EF001435)
690 V
Rated permanent current I_u (EF001389)
25 A
Rated permanent current at AC-23, 400 V (EF011777)
25 A
Rated permanent current at AC-21, 400 V (EF009165)
25 A
Rated operation power at AC-3, 400 V (EF001364)
7.5 kW
Rated short-time withstand current I_{cw} (EF007050)
0.64 kA
Rated operation power at AC-23, 400 V (EF007027)
13 kW
Switching power at 400 V (EF009166)
13 kW
Conditioned rated short-circuit current I_q (EF001444)
80 kA
Number of poles (EF001391)
3
Number of auxiliary contacts as normally closed contact (EF001377)
1
Number of auxiliary contacts as normally open contact (EF001376...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-25/I2/HI11-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.