

INDUSTRIAL COMPONENT DATA

P1-25/SE1/N 197345 Y7-197345 EATON ELECTRIC On-Off switch 25 A 3+N surface mounting with black handle and

Brand: EATON - MOELLER | Manufacturer Part Number: P1-25/SE1/N



Manufacturer	EATON - MOELLER
MPN / Reference	P1-25/SE1/N
Catalog number	Y7-197345
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-134DC50CC6
Generated	2026-08-04

Product Overview

On-Off switch; 25 A; 3+N; surface mounting; with black handle and P1-25/SE1/N

On-Off switch, P1, 25 A, 3 pole + N, surface mounting, with black thumb grip and front plate, in steel enclosure

On-Off switch, P1, Rated uninterrupted current (Iu): 25 A, Fitted with: Black thumb grip and front plate, Mounting method: Surface mounting, Number of poles: Three-pole, Degree of Protection: NEMA 12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

On-Off switch, P1, 25 A, 3 pole + N, surface mounting, with black thumb grip and front plate, in steel enclosure
On-Off switch, P1, Rated uninterrupted current (Iu): 25 A, Fitted with: Black thumb grip and front plate, Mounting method: Surface mounting, Number of poles: Three-pole, Degree of Protection: NEMA 12

General specificationsProduct nameEaton Moeller® series P1 On-Off switchPart

no.P1-25/SE1/NEAN4015080896913Product Length/Depth200 millimetreProduct height127 millimetreProduct width150 millimetreProduct weight1.675 kilogramCertificationsIEC/EN 60947-3

IEC/EN 60204

VDE 0660

IEC/EN 60947Product TradenameP1Product TypeOn-Off switchProduct Sub TypeNoneCatalog Notesin steel enclosure

Rated Short-time Withstand Current (Icw) for a time of 1 secondFeatures & FunctionsFeaturesVersion as maintenance-/service switchFitted with:Black thumb grip and front plateNumber of polesThree-poleGeneral

informationAccessoriesAuxiliary contact fitted by user.Degree of protectionNEMA 12Degree of protection (front side)IP65Lifespan, mechanical300,000 OperationsMounting methodSurface mountingMounting positionAs requiredOperating frequency1200 Operations/hOvervoltage categoryIIIPollution degree3Rated impulse withstand voltage (Uimp)6000 V ACsafe isolation440 V AC, Between the contacts, According to EN 61140Safety parameter (EN ISO 13849-1)B10d values as per EN ISO 13849-1, table C.1Shock resistance15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 msSuitable forGround mou...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-25/SE1/N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.