

## INDUSTRIAL COMPONENT DATA

# P1-25/SE1/SVB/N 197348 Y7-197348 EATON ELECTRIC

## P1-25/SE1/SVB/N

Brand: EATON - MOELLER | Manufacturer Part Number: P1-25/SE1/SVB/N



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | P1-25/SE1/SVB/N     |
| Catalog number  | Y7-197348           |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-8B29523F09       |
| Generated       | 2026-08-06          |

## Product Overview

P1-25/SE1/SVB/N

Eaton Moeller® series P1 Main switch, P1, 25 A, surface mounting, 3 pole + N, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) position, in steel enclosure

Main switch, P1, Rated uninterrupted current (I<sub>u</sub>): 25 A, Functions: Emergency switching off function, Interlockable, Fitted with: Red rotary handle and yellow locking ring, Mounting method: Surface mounting, Number of poles: Four-pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: NEMA 12

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                  |
|--------------|--------------------------------------------------|
| Catalog path | EATON - MOELLER > Disconnectors and Cam Switches |
|--------------|--------------------------------------------------|

## Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 Main switch Catalog Number 197348 Model Code P1-25/SE1/SVB/N EAN

4015080894858 Product Length/Depth 200 mm Product Height 135 mm Product Width 150 mm Product Weight 1.725 kg

Certifications VDE 0660

IEC/EN 60947

IEC/EN 60947-3

IEC/EN 60204 Features &amp; Functions

Features Version as emergency stop installation

Version as maintenance-/service switch

Version as main switch

Version as safety switch Fitted with: Red rotary handle and yellow locking ring Functions Emergency switching off function Interlockable Locking facility Lockable in the 0 (Off) position Number of poles Four-pole General Accessories Auxiliary contact fitted by user. Degree of protection NEMA 12 Degree of protection (front side) IP65 Lifespan, mechanical 300,000 Operations Mounting method Surface mounting Mounting position As required Operating frequency 1200 Operations/h Overvoltage category III Pollution degree 3 Product Category Main switch Rated impulse withstand voltage (Uimp) 6000 V AC Safe isolation 440 V AC, Between the contacts, According to EN 61140 Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1 Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms Suitable for Ground mounting Switching angle 90 ° Climatic environmental conditions Ambient operating temperature (enclosed) - min -25 °C Ambient operating temperature (enclosed) - max 40 °C Terminal capacities Terminal capacit...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-25/SE1/SVB/N with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.