

INDUSTRIAL COMPONENT DATA

P1-25/SE1/SVB-SW/HI11 197350 Y7-197350 EATON ELECTRIC P1-25/SE1/SVB-SW/HI11

Brand: EATON - MOELLER | Manufacturer Part Number: P1-25/SE1/SVB-SW/HI11



Manufacturer	EATON - MOELLER
MPN / Reference	P1-25/SE1/SVB-SW/HI11
Catalog number	Y7-197350
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-D361085F84
Generated	2026-08-06

Product Overview

P1-25/SE1/SVB-SW/HI11

Eaton Moeller® series P1 Main switch, P1, 25 A, surface mounting, 3 pole, 1 N/O, 1 N/C, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position, in steel enclosure

Main switch, P1, Rated uninterrupted current (I_u): 25 A, Functions: STOP function, Interlockable, Fitted with: Black rotary handle and locking ring, Mounting method: Surface mounting, Number of poles: Three-pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: NEMA 12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 Main switch

Catalog Number 197350

Model Code P1-25/SE1/SVB-SW/HI11

EAN 4015080894872

Product Length/Depth 200 mm

Product Height 135 mm

Product Width 150 mm

Product Weight 1.7 kg

Certifications IEC/EN 60947-3

IEC/EN 60204

IEC/EN 60947

VDE 0660

Features & Functions

Features Version as maintenance-/service switch

Version as main switch

Fitted with: Black rotary handle and locking ring

Functions STOP function

Interlockable

Locking facility Lockable in the 0 (Off) position

Number of poles Three-pole

General information

Accessories Auxiliary contact or neutral conductor fitted by user.

Degree of protection NEMA 12

Degree of protection (front side) IP65

Lifespan, mechanical 300,000 Operations

Mounting method Surface mounting

Mounting position As required

Operating frequency 1200 Operations/h

Overvoltage category III

Pollution degree 3

Product Category Main switch

Product Category Main switch

Rated impulse withstand voltage (Uimp) 6000 V AC

Safe isolation 440 V AC, Between the contacts, According to EN 61140

Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1

Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms

Suitable for Ground mounting

Switching angle 90 °

Climatic environmental conditions

Ambient operating temperature (enclosed) - min -25 °C

Ambient operating temperature (enclosed) - max 40 °C

Terminal capacities

Screw size M4, Terminal screw

Tighten...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-25/SE1/SVB-SW/HI11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.