

INDUSTRIAL COMPONENT DATA

P1-25/SE1/SVB-SW/N 197351 Y7-197351 EATON ELECTRIC P1-25/SE1/SVB-SW/N

Brand: EATON - MOELLER | Manufacturer Part Number: P1-25/SE1/SVB-SW/N

Manufacturer	EATON - MOELLER
MPN / Reference	P1-25/SE1/SVB-SW/N
Catalog number	Y7-197351
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-0BB50A497E
Generated	2026-08-06

Product Overview

P1-25/SE1/SVB-SW/N

Eaton Moeller® series P1 Main switch, P1, 25 A, surface mounting, 3 pole + N, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position, in steel enclosure

Main switch, P1, Rated uninterrupted current (I_u): 25 A, Functions: Interlockable, STOP function, Fitted with: Black rotary handle and locking ring, Mounting method: Surface mounting, Number of poles: Four-pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: NEMA 12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 Main switch Catalog Number 197351 Model Code P1-25/SE1/SVB-SW/N EAN 4015080894889 Product Length/Depth 200 mm Product Height 135 mm Product Width 150 mm Product Weight 1.725 kg Certifications VDE 0660

IEC/EN 60947

IEC/EN 60204

IEC/EN 60947-3 Features & Functions

Features Version as maintenance-/service switch

Version as main switch Fitted with: Black rotary handle and locking ring Functions STOP function

Interlockable Locking facility Lockable in the 0 (Off) position Number of poles Four-pole General

Accessories Auxiliary contact fitted by user. Degree of protection NEMA 12 Degree of protection (front side) IP65 Lifespan, mechanical 300,000 Operations Mounting method Surface mounting Mounting position As required Operating frequency 1200 Operations/h Overvoltage category III Pollution degree 3 Product Category Main switch Rated impulse withstand voltage (Uimp) 6000 V AC Safe isolation 440 V AC, Between the contacts, According to EN 61140 Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1 Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms Suitable for Ground mounting Switching angle 90 ° Climatic environmental conditions

Ambient operating temperature (enclosed) - min -25 °C Ambient operating temperature (enclosed) - max 40 °C Terminal capacities

Terminal capacity 1 x (1.5 - 6) mm², solid or stranded

2 x (1.5 - 6) mm², solid or stranded

2 x (1 -....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-25/SE1/SVB-SW/N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.