

INDUSTRIAL COMPONENT DATA

P1-32/I2H/MBS/SVB/HI11 182419 Y7-182419 EATON ELECTRIC Main switch, 3p+1S+1Ö,32A,Emergency-Stop function,loc..

Brand: EATON - MOELLER | Manufacturer Part Number: P1-32/I2H/MBS/SVB/HI11



Manufacturer	EATON - MOELLER
MPN / Reference	P1-32/I2H/MBS/SVB/HI11
Catalog number	Y7-182419
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-0A2B8D31AC
Generated	2026-08-04

Product Overview

Main switch, 3p+1S+1Ö,32A,Emergency-Stop function,lockable in the 0 (Off) position,surface mounting,hard knockout version,with mounting plate screen

P1-32/I2H/MBS/SVB/HI11

Main switch, P1, 32 A, surface mounting, 3 pole, 1 N/O, 1 N/C, Emergency switching off function, Lockable in the 0 (Off) position, hard knockout version, with assembly sheet screen

Main switch, P1, Rated uninterrupted current (Iu): 32 A, Functions: Interlockable, Emergency switching off function, Fitted with: Red rotary handle and yellow locking ring, Assembly sheet screen, Mounting method: Surface mounting, Number of poles: Three-pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: NEMA 12 , Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

EL-Nummer (Norway)0001400418Main switch, P1, 32 A, surface mounting, 3 pole, 1 N/O, 1 N/C, Emergency switching off function, Lockable in the 0 (Off) position, hard knockout version, with assembly sheet screenMain switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: P1, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, Notes: hard knockout version, with assembly sheet screen, Information about equipment supplied: Auxiliary contact or neutral conductor fitted by user., 3 pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP65, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: Iu = 32 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector

according to IEC/EN 60947-3 Delivery program

Product range Main switch

maintenance switch

Repair switch Part group reference P1 Stop Function Emergency switching off function With red rotary handle and yellow locking ring Information about equipment supplied Auxiliary contact or neutral conductor fitted by user. Notes hard knockout version

with assembly sheet screen Number of poles 3 pole Auxiliary contacts 1 N/O 1 N/C Locking facility Lockable in the 0 (Off) position Degree of Protection IP65 Design surface mounting Contact sequence Function Motor rating AC-23A, 50 - 60 Hz [P] 400 V [P] 15 kW Rated uninterrupted current [I_u] 32 A Note on rated uninterrupted current I_u Rated uninterrupted....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-32/I2H/MBS/SVB/HI11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.