

INDUSTRIAL COMPONENT DATA

P1-32/SE1/SVB/HI11 197355 EATON ELECTRIC General Switch. 32A. surface mounting. 3p. 1NO+1NC.

Brand: EATON - MOELLER | Manufacturer Part Number: P1-32/SE1/SVB/HI11



Manufacturer	EATON - MOELLER
MPN / Reference	P1-32/SE1/SVB/HI11
Catalog number	Y7-197355
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-EC1C64BB37
Generated	2026-08-04

Product Overview

General Switch. 32A. surface mounting. 3p. 1NO+1NC.

Main switch, P1, Rated uninterrupted current (Iu): 32 A, Functions: Interlockable, Emergency switching off function, Fitted with: Red rotary handle and yellow locking ring, Mounting method: Surface mounting, Number of poles: Three-pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: NEMA 12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 Main switch Catalog Number 197355 Model Code P1-32/SE1/SVB/HI11 EAN 4015080896890 Product Length/Depth 200 mm Product Height 135 mm Product Width 150 mm Product Weight 1.7 kg

Certifications VDE 0660

IEC/EN 60947-3

IEC/EN 60204

IEC/EN 60947 Features & Functions

Features Version as maintenance-/service switch

Version as safety switch

Version as main switch

Version as emergency stop installation Fitted with: Red rotary handle and yellow locking ring Functions Emergency switching off function

Interlockable Locking facility Lockable in the 0 (Off) position Number of poles Three-pole General
Accessories Auxiliary contact or neutral conductor fitted by user. Degree of protection NEMA 12 Degree of protection (front side) IP65 Lifespan, mechanical 300,000 Operations Mounting method Surface mounting Mounting position As required
Operating frequency 1200 Operations/h Overvoltage category III Pollution degree 3 Product Category Main switch Rated impulse withstand voltage (Uimp) 6000 V AC Safe isolation 440 V AC, Between the contacts, According to EN 61140 Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1 Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms Suitable for Ground mounting Switching angle 90 ° Climatic environmental conditions
Ambient operating temperature (enclosed) - min -25 °C Ambient operating temperature (enclosed) - max 40 °C Terminal capa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-32/SE1/SVB/HI11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.