

INDUSTRIAL COMPONENT DATA

P1-40/E/HI11 199890 Y7-199890 EATON ELECTRIC

P1-40/E/HI11

Brand: EATON - MOELLER | Manufacturer Part Number: P1-40/E/HI11



Manufacturer	EATON - MOELLER
MPN / Reference	P1-40/E/HI11
Catalog number	Y7-199890
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-D4A36BBA3C
Generated	2026-08-05

Product Overview

P1-40/E/HI11

Eaton Moeller® series P1 On-Off switch, 40 A, flush mounting, 3 pole, 1 N/O, 1 N/C, with black thumb grip and front plate
On-Off switch, P1, Rated uninterrupted current (Iu): 40 A, Fitted with: Black thumb grip and front plate, Mounting method:
Flush mounting, Number of poles: Three-pole, Degree of Protection: IP65

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 On-off switch Catalog Number 199890 Model Code P1-40/E/HI11 EAN 4015082953317 Product Length/Depth 75 mm Product Height 70 mm Product Width 49 mm Product Weight 0.183 kg

Compliances UKCA

CE Certifications IEC/EN 60947

IEC/EN 60947-3

IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 199890 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

No

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Max. rated operation voltage U_e AC (EF007355)

690 V

Rated operating voltage (EF001435)

690 V

Rated permanent current I_u (EF001389)

40 A

Rated permanent current at AC-23, 400 V (EF011777)

40 A

Rated permanent current at AC-21, 400 V (EF009165)

40 A

Rated operation power at AC-3, 400 V (EF001364)

15 kW

Rated short-time withstand current I_{cw} (EF007050)

0.64 kA

Rated operation power at AC-23, 400 V (EF007027)

22 kW

Switching power at 400 V (EF009166)

22 kW

Conditioned rated short-circuit current I_q (EF001444)

80 kA

Number of poles (EF001391)

3

Number of auxiliary contacts as normally closed contact (EF001377)

1

Number of auxiliary contacts as normally open contact (EF001376)

1

Number of auxiliary contacts as change-over contact (EF003531)

0

Motor driv...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-40/E/HI11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.