

INDUSTRIAL COMPONENT DATA

P1-40/I2/SVB/HI11 199910 Y7-199910 EATON ELECTRIC

P1-40/I2/SVB/HI11

Brand: EATON - MOELLER | Manufacturer Part Number: P1-40/I2/SVB/HI11



Manufacturer	EATON - MOELLER
MPN / Reference	P1-40/I2/SVB/HI11
Catalog number	Y7-199910
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-862AD24B05
Generated	2026-08-06

Product Overview

P1-40/I2/SVB/HI11

Main switch, P1, 40 A, surface mounting, 3 pole, 1 N/O, 1 N/C, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) position

Main switch, P1, Rated uninterrupted current (Iu): 40 A, Functions: Emergency switching off function, Interlockable, Fitted with: Red rotary handle and yellow locking ring, Mounting method: Surface mounting, Number of poles: Three-pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP65

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Main switch, P1, 40 A, surface mounting, 3 pole, 1 N/O, 1 N/C, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) positionMain switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: P1, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, Information about equipment supplied: Auxiliary contact or neutral conductor fitted by user., 3 pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP65, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V : P = 22 kW, Rated uninterrupted current: Iu = 40 A, Standards: IEC/EN 60947, IEC/EN 60204,

Switch-disconnector according to IEC/EN 60947-3Delivery program

Product rangeMain switch

maintenance switchPart group referenceP1Stop FunctionEmergency switching off functionWith red rotary handle and yellow locking ringNumber of poles3 poleAuxiliary contacts1 N/O1 N/CLocking facilityLockable in the 0 (Off) positionDegree of

ProtectionIP65Designsurface mountingContact sequenceSwitching angle90 °FunctionMotor rating AC-23A, 50 - 60 Hz
[P]400 V [P]22 kWRated uninterrupted current [I_u]40 ANote on rated uninterrupted current !uRated uninterrupted current
I_u is specified for max. cross-section.Technical data
GeneralStandardsIEC/EN 60947, IEC/EN 60204
Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 600...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-40/I2/SVB/HI11 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.