

INDUSTRIAL COMPONENT DATA

P1-40/I2/SVB/N 199911 Y7-199911 EATON ELECTRIC

P1-40/I2/SVB/N

Brand: EATON - MOELLER | Manufacturer Part Number: P1-40/I2/SVB/N



Manufacturer	EATON - MOELLER
MPN / Reference	P1-40/I2/SVB/N
Catalog number	Y7-199911
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-436C3B62EF
Generated	2026-08-05

Product Overview

P1-40/I2/SVB/N

Eaton Moeller® series P1 Main switch, 40 A, surface mounting, 3 pole + N, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) position

Main switch, P1, Rated uninterrupted current (I_u): 40 A, Functions: Emergency switching off function, Interlockable, Fitted with: Red rotary handle and yellow locking ring, Auxiliary contact, Mounting method: Surface mounting, Number of poles: Three-pole + N, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP65

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 Main switch Catalog Number 199911 Model Code P1-40/I2/SVB/N EAN

4015082953386 Product Length/Depth 115 mm Product Height 180 mm Product Width 100 mm Product Weight 0.586 kg

Compliances UKCA

CE Certifications IEC/EN 60947

IEC/EN 60947-3

IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 199911 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)
Yes
Version as maintenance-/service switch (EF006986)
Yes
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
Yes
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Max. rated operation voltage U_e AC (EF007355)
690 V
Rated operating voltage (EF001435)
690 V
Rated permanent current I_u (EF001389)
40 A
Rated permanent current at AC-23, 400 V (EF011777)
40 A
Rated permanent current at AC-21, 400 V (EF009165)
40 A
Rated operation power at AC-3, 400 V (EF001364)
15 kW
Rated short-time withstand current I_{cw} (EF007050)
0.64 kA
Rated operation power at AC-23, 400 V (EF007027)
22 kW
Switching power at 400 V (EF009166)
22 kW
Conditioned rated short-circuit current I_q (EF001444)
80 kA
Number of poles (EF001391)
4
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as change-over contact (EF003531)
0
Moto...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-40/I2/SVB/N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.