

## INDUSTRIAL COMPONENT DATA

# P1-40/I2H/SVB-SW 199925 Y7-199925 EATON ELECTRIC

## P1-40/I2H/SVB-SW

Brand: EATON - MOELLER | Manufacturer Part Number: P1-40/I2H/SVB-SW



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | P1-40/I2H/SVB-SW    |
| Catalog number  | Y7-199925           |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-30709A845B       |
| Generated       | 2026-08-04          |

### Product Overview

P1-40/I2H/SVB-SW

Eaton Moeller® series P1 Main switch, 40 A, surface mounting, 3 pole, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position, hard knockout version

Main switch, P1, Rated uninterrupted current (Iu): 40 A, Functions: Interlockable, STOP function, Fitted with: Red rotary handle and yellow locking ring, Auxiliary contact, Mounting method: Surface mounting, Number of poles: Three-pole + N, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP65

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Disconnectors and Cam Switches

### Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 Main switch Catalog Number 199925 Model Code P1-40/I2H/SVB-SW EAN 4015082953287 Product Length/Depth 115 mm Product Height 180 mm Product Width 100 mm Product Weight 0.556 kg

Compliances UKCA

CE Certifications IEC/EN 60947

IEC/EN 60947-3

IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 199925 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)  
Yes  
Version as maintenance-/service switch (EF006986)  
Yes  
Version as safety switch (EF006985)  
No  
Version as emergency stop installation (EF006959)  
Yes  
Version as reversing switch (EF009408)  
No  
Number of switches (EF005586)  
1  
Max. rated operation voltage  $U_e$  AC (EF007355)  
690 V  
Rated operating voltage (EF001435)  
690 V  
Rated permanent current  $I_u$  (EF001389)  
40 A  
Rated permanent current at AC-23, 400 V (EF011777)  
40 A  
Rated permanent current at AC-21, 400 V (EF009165)  
40 A  
Rated operation power at AC-3, 400 V (EF001364)  
15 kW  
Rated short-time withstand current  $I_{cw}$  (EF007050)  
0.64 kA  
Rated operation power at AC-23, 400 V (EF007027)  
22 kW  
Switching power at 400 V (EF009166)  
22 kW  
Conditioned rated short-circuit current  $I_q$  (EF001444)  
80 kA  
Number of auxiliary contacts as normally closed contact (EF001377)  
0  
Number of auxiliary contacts as normally open contact (EF001376)  
0  
Number of auxiliary contacts as change-over contact (EF003531)  
0  
Motor drive optional (EF007386)...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-40/I2H/SVB-SW with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.