

INDUSTRIAL COMPONENT DATA

P1-40/M4/SVB-SW/N 199942 Y7-199942 EATON ELECTRIC P1-40/M4/SVB-SW/N

Brand: EATON - MOELLER | Manufacturer Part Number: P1-40/M4/SVB-SW/N



Manufacturer	EATON - MOELLER
MPN / Reference	P1-40/M4/SVB-SW/N
Catalog number	Y7-199942
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-F8E3374170
Generated	2026-08-05

Product Overview

P1-40/M4/SVB-SW/N

Eaton Moeller® series P1 Main switch, 40 A, rear mounting, 3 pole + N, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position, With metal shaft for a control panel depth of 400 mm

Main switch, P1, Rated uninterrupted current (I_u): 40 A, Functions: STOP function, Interlockable, Fitted with: Black rotary handle and locking ring, Metal shaft for a control panel depth of 400 mm, Auxiliary contact, Mounting method: Rear mounting, Number of poles: Three-pole + N, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP65

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 Main switch Catalog Number 199942 Model Code P1-40/M4/SVB-SW/N EAN 4015082953584 Product Length/Depth 340 mm Product Height 70 mm Product Width 72 mm Product Weight 0.34 kg

Compliances UKCA

CE Certifications IEC/EN 60947

IEC/EN 60947-3

IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 199942 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)
Yes

Version as maintenance-/service switch (EF006986)
Yes

Version as safety switch (EF006985)
No

Version as emergency stop installation (EF006959)
No

Version as reversing switch (EF009408)
No

Number of switches (EF005586)
1

Max. rated operation voltage U_e AC (EF007355)
690 V

Rated operating voltage (EF001435)
690 V

Rated permanent current I_u (EF001389)
40 A

Rated permanent current at AC-23, 400 V (EF011777)
40 A

Rated permanent current at AC-21, 400 V (EF009165)
40 A

Rated operation power at AC-3, 400 V (EF001364)
15 kW

Rated short-time withstand current I_{cw} (EF007050)
0.64 kA

Rated operation power at AC-23, 400 V (EF007027)
22 kW

Switching power at 400 V (EF009166)
22 kW

Conditioned rated short-circuit current I_q (EF001444)
80 kA

Number of auxiliary contacts as normally closed contact (EF001377)
0

Number of auxiliary contacts as normally open contact (EF001376)
0

Number of auxiliary contacts as change-over contact (EF003531)
0

Motor drive optional (EF007386)
No...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-40/M4/SVB-SW/N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.