

INDUSTRIAL COMPONENT DATA

**P1-40/M4/SVB-SW/N/HI11 199943 Y7-199943 EATON
ELECTRIC P1-40/M4/SVB-SW/N/HI11**

Brand: EATON - MOELLER | Manufacturer Part Number: P1-40/M4/SVB-SW/N/HI11



Manufacturer	EATON - MOELLER
MPN / Reference	P1-40/M4/SVB-SW/N/HI11
Catalog number	Y7-199943
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-5B36A195CD
Generated	2026-08-06

Product Overview

P1-40/M4/SVB-SW/N/HI11

Eaton Moeller® series P1 Main switch, 40 A, rear mounting, 3 pole + N, 1 N/O, 1 N/C, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position, With metal shaft for a control panel depth of 400 mm

Main switch, P1, Rated uninterrupted current (I_u): 40 A, Functions: STOP function, Interlockable, Fitted with: Black rotary handle and locking ring, Metal shaft for a control panel depth of 400 mm, Mounting method: Rear mounting, Number of poles: Three-pole + N, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP65

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 Main switch Catalog Number 199943 Model Code P1-40/M4/SVB-SW/N/HI11
EAN 4015082953591 Product Length/Depth 340 mm Product Height 70 mm Product Width 86 mm Product Weight 0.385 kg
Compliances UKCA
CE Certifications IEC/EN 60947
IEC/EN 60947-3
IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second
ETIM for 199943 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value

Version as main switch (EF006981)
Yes

Version as maintenance-/service switch (EF006986)
Yes

Version as safety switch (EF006985)
No

Version as emergency stop installation (EF006959)
No

Version as reversing switch (EF009408)
No

Number of switches (EF005586)
1

Max. rated operation voltage U_e AC (EF007355)
690 V

Rated operating voltage (EF001435)
690 V

Rated permanent current I_u (EF001389)
40 A

Rated permanent current at AC-23, 400 V (EF011777)
40 A

Rated permanent current at AC-21, 400 V (EF009165)
40 A

Rated operation power at AC-3, 400 V (EF001364)
15 kW

Rated short-time withstand current I_{cw} (EF007050)
0.64 kA

Rated operation power at AC-23, 400 V (EF007027)
22 kW

Switching power at 400 V (EF009166)
22 kW

Conditioned rated short-circuit current I_q (EF001444)
80 kA

Number of auxiliary contacts as normally closed contact (EF001377)
1

Number of auxiliary contacts as normally open contact (EF001376)
1

Number of auxiliary contacts as change-over contact (EF003531)
0

Motor drive optional (EF0073...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-40/M4/SVB-SW/N/Hi11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.