

INDUSTRIAL COMPONENT DATA

P1-40/V/SVB 199952 Y7-199952 EATON ELECTRIC

P1-40/V/SVB

Brand: EATON - MOELLER | Manufacturer Part Number: P1-40/V/SVB



Manufacturer	EATON - MOELLER
MPN / Reference	P1-40/V/SVB
Catalog number	Y7-199952
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-5371567433
Generated	2026-08-05

Product Overview

P1-40/V/SVB

Main switch, P1, 40 A, rear mounting, 3 pole, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) position

Main switch, P1, Rated uninterrupted current (Iu): 40 A, Functions: Emergency switching off function, Interlockable, Fitted with: Red rotary handle and yellow locking ring, Auxiliary contact, Mounting method: Rear mounting, Number of poles: Three-pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP65

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Main switch, P1, 40 A, rear mounting, 3 pole, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) positionMain switch, P1, Rated uninterrupted current (Iu): 40 A, Functions: Emergency switching off function, Interlockable, Fitted with: Red rotary handle and yellow locking ring, Auxiliary contact, Mounting method: Rear mounting, Number of poles: Three-pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP65

General specificationsProduct nameEaton Moeller® series P1 Main switchPart

no.P1-40/V/SVBEAN4015082953027Product Length/Depth90 millimetreProduct height70 millimetreProduct width54 millimetreProduct weight0.265 kilogramCompliancesUKCA

CECertificationsIEC/EN 60204

IEC/EN 60947

IEC/EN 60947-3Product TradenameP1Product TypeMain switchProduct Sub TypeNoneCatalog NotesRated Short-time
Withstand Current (Icw) for a time of 1 secondFeatures & FunctionsFeaturesVersion as main switch
Version as maintenance-/service switch
Version as emergency stop installationFitted with:Red rotary handle and yellow locking ring
Auxiliary contactFunctionsEmergency switching off function
InterlockableLocking facilityLockable in the 0 (Off) positionNumber of poles3General informationDegree of
protectionIP65Degree of protection (front side)IP65Lifespan, mechanical300,000 OperationsMounting methodRear
mountingMounting positionAs requiredOperating frequency50 Operations/hOvervoltage categoryIIIPollution degree3Rated
impuls...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-40/V/SVB with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.