

INDUSTRIAL COMPONENT DATA

P1-40/V/SVB-SW/N 199961 Y7-199961 EATON ELECTRIC

P1-40/V/SVB-SW/N

Brand: EATON - MOELLER | Manufacturer Part Number: P1-40/V/SVB-SW/N



Manufacturer	EATON - MOELLER
MPN / Reference	P1-40/V/SVB-SW/N
Catalog number	Y7-199961
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-B649021500
Generated	2026-08-05

Product Overview

P1-40/V/SVB-SW/N

Main switch, P1, 40 A, rear mounting, 3 pole + N, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position

Main switch, P1, Rated uninterrupted current (Iu): 40 A, Functions: STOP function, Interlockable, Fitted with: Black rotary handle and locking ring, Auxiliary contact, Mounting method: Rear mounting, Number of poles: Three-pole + N, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP65

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

Main switch, P1, 40 A, rear mounting, 3 pole + N, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) positionMain switch, P1, Rated uninterrupted current (Iu): 40 A, Functions: STOP function, Interlockable, Fitted with: Black rotary handle and locking ring, Auxiliary contact, Mounting method: Rear mounting, Number of poles: Three-pole + N, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP65

General specificationsProduct nameEaton Moeller® series P1 Main switchPart

no.P1-40/V/SVB-SW/NEAN4015082952969Product Length/Depth90 millimetreProduct height70 millimetreProduct width63 millimetreProduct weight0.295 kilogramCompliancesUKCA

CECertificationsIEC/EN 60947-3

IEC/EN 60947

IEC/EN 60204Product TradenameP1Product TypeMain switchProduct Sub TypeNoneCatalog NotesRated Short-time

Withstand Current (Icw) for a time of 1 second
Features & Functions
Version as main switch
Version as maintenance-/service switch
Fitted with: Black rotary handle and locking ring
Auxiliary contact
Functions STOP function
Interlockable
Locking facility
Lockable in the 0 (Off) position
Number of poles 3+N
General information
Accessories
Auxiliary contact fitted by user.
Degree of protection IP65
Degree of protection (front side) IP65
Lifespan, mechanical 300,000
Operations
Mounting method Rear mounting
Mounting position As required
Operating frequency 50 Operations/h
Overvoltage category III
Pollution degree 3
Rated impulse withstand voltage (Uimp) 6000 V AC
Safe isolation 440...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-40/V/SVB-SW/N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.