

## INDUSTRIAL COMPONENT DATA

## P1-40/Z 199964 Y7-199964 EATON ELECTRIC P1-40/Z

Brand: EATON - MOELLER | Manufacturer Part Number: P1-40/Z



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | P1-40/Z             |
| Catalog number  | Y7-199964           |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-B1A6C23AEF       |
| Generated       | 2026-08-03          |

## Product Overview

P1-40/Z

Eaton Moeller® series P1 On-Off switch, 40 A, rear mounting, 3 pole, with black thumb grip and front plate  
On-Off switch, P1, Rated uninterrupted current (Iu): 40 A, Fitted with: Black thumb grip and front plate, Auxiliary contact,  
Mounting method: Rear mounting, Number of poles: Three-pole, Degree of Protection: IP65

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path EATON - MOELLER &gt; Disconnectors and Cam Switches

## Additional Product Information

## General specifications

Product Name Eaton Moeller® series P1 On-off switch Catalog Number 199964 Model Code P1-40/Z EAN 4015082953065  
Product Length/Depth 130 mm Product Height 70 mm Product Width 49 mm Product Weight 0.131 kg Compliances UKCA  
CE Certifications IEC/EN 60947

IEC/EN 60947-3

IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 199964 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)  
No  
Version as emergency stop installation (EF006959)  
No  
Version as reversing switch (EF009408)  
No  
Number of switches (EF005586)  
1  
Max. rated operation voltage Ue AC (EF007355)  
690 V  
Rated operating voltage (EF001435)  
690 V  
Rated permanent current Iu (EF001389)  
40 A  
Rated permanent current at AC-23, 400 V (EF011777)  
40 A  
Rated permanent current at AC-21, 400 V (EF009165)  
40 A  
Rated operation power at AC-3, 400 V (EF001364)  
15 kW  
Rated short-time withstand current Icw (EF007050)  
0.64 kA  
Rated operation power at AC-23, 400 V (EF007027)  
22 kW  
Switching power at 400 V (EF009166)  
22 kW  
Conditioned rated short-circuit current Iq (EF001444)  
80 kA  
Number of poles (EF001391)  
3  
Number of auxiliary contacts as normally closed contact (EF001377)  
0  
Number of auxiliary contacts as normally open contact (EF001376)  
0  
Number of auxiliary contacts as change-over contact (EF003531)  
0  
Motor drive op...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-40/Z with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.