

## INDUSTRIAL COMPONENT DATA

# P3-100/ST/SVB-SW 201717 EATON ELECTRIC Main switch, +steel enclosure, 3p, 100A, handle black, lockable

Brand: EATON - MOELLER | Manufacturer Part Number: P3-100/ST/SVB-SW



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | P3-100/ST/SVB-SW    |
| Catalog number  | 201717              |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-93DE08C946       |
| Generated       | 2026-08-03          |

## Product Overview

Main switch, +steel enclosure, 3p, 100A, handle black, lockable

General switch; 3-pole; 100a; Mounting stainless steel box; Lever Black; Lockable in the 0 position (OFF)

Main switch/switch-disconnector on-off according to IEC/EN 60947-3, 690V/100A, steel sheet enclosure, degree of protection Front IP55, handle black with black locking collar lockable with 3 padlocks, switch-disconnectors P3 have a very compact and robust design. The manual drive act directly to the connection of the contacts. The contacts are forced open when switching off. Design general: insulating material-surface mounting enclosure, flush mounting, rear mounting, IVS service distribution board mounting

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

## Additional Product Information

Main switch, +steel enclosure, 3p, 100A, handle black, lockableMain switch/switch-disconnector on-off according to IEC/EN 60947-3, 690V/100A, steel sheet enclosure, degree of protection Front IP55, handle black with black locking collar lockable with 3 padlocks, switch-disconnectors P3 have a very compact and robust design. The manual drive act directly to the connection of the contacts. The contacts are forced open when switching off. Design general: insulating material-surface mounting enclosure, flush mounting, rear mounting, IVS service distribution board mountingTechnical data ETIM 4.0

Version as switch disconnecter compactYesVersion as main switchYesVersion as maintenance-/service switchYesVersion as safety switchNoVersion as emergency stop installationNoMax. rated operation voltage Ue AC690 VRated permanent current Iu100 ARated operation power AC-3, 400 V37 kWRated operation power at AC-23, 400V50 kWConditioned rated short-circuit current Iq0 kANumber of poles3Number of auxiliary contacts as normally closed contact0Number of auxiliary

contacts as normally open contact0Number of auxiliary contacts as change-over contact0Motor drive optionalNoMotor drive integratedNoVoltage release optionalNoDevice constructionBuilt-in device fixed built-in techniqueSuitable for ground mountingNoSuitable for front mountingNoSuitable for front mounting centerNoSuitable for distribution board installationNoSuitable for intermediate mountingNoType of control element-InterlockableYesConnect...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P3-100/ST/SVB-SW with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.