

INDUSTRIAL COMPONENT DATA

P3-30/EA/SVB-SW-MCS 237893 Y7-237893 EATON ELECTRIC 001628 +R1/4"-MCSN

Brand: EATON - MOELLER | Manufacturer Part Number: P3-30/EA/SVB-SW-MCS



Manufacturer	EATON - MOELLER
MPN / Reference	P3-30/EA/SVB-SW-MCS
Catalog number	Y7-237893
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-C9AA56564C
Generated	2026-08-01

Product Overview

001628 +R1/4"-MCSN

P3-30/EA/SVB-SW-MCS

Eaton Moeller® series P3 Main switch, P3, 30 A, flush mounting, 3 pole, With black rotary handle and locking ring, Lockable in the 0 (Off) position, UL/CSA

Main switch, Product range: Main switch, maintenance switch, Part group reference: P3, With black rotary handle and locking ring, 3 pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: Front IP65, Design: flush mounting, Rated uninterrupted current: Iu = 30 A, Standards: UL489

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series P3 Main switch Catalog Number 237893 Model Code P3-30/EA/SVB-SW-MCS EAN 4015082378936 Product Length/Depth 150 mm Product Height 114 mm Product Width 90 mm Product Weight 0.374 kg

Certifications UL

CSA

UL489

UL 489

UL File No.: E148671

CSA File No.: 1342868 (LR12528)

ETIM for 237893 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

Yes

Version as maintenance-/service switch (EF006986)

Yes

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

No

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Max. rated operation voltage Ue AC (EF007355)

480 V

Rated operating voltage (EF001435)

690 V

Rated permanent current Iu (EF001389)

30 A

Rated permanent current at AC-21, 400 V (EF009165)

0 A

Rated operation power at AC-3, 400 V (EF001364)

0 kW

Rated short-time withstand current Icw (EF007050)

0 kA

Rated operation power at AC-23, 400 V (EF007027)

0 kW

Switching power at 400 V (EF009166)

0 kW

Conditioned rated short-circuit current Iq (EF001444)

100 kA

Number of poles (EF001391)

3

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Motor drive optional (EF007386)

No

Motor drive integrated (EF006697)

No

Voltage release optional (EF007491)

No

Device constructio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P3-30/EA/SVB-SW-MCS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.