

INDUSTRIAL COMPONENT DATA

P3-63/I3/SVB/N/HI11 207342 Y7-207342 EATON ELECTRIC Main switch, +housing, 3p+N+1N/O+1N/C, 63A, handle red y..

Brand: EATON - MOELLER | Manufacturer Part Number: P3-63/I3/SVB/N/HI11



Manufacturer	EATON - MOELLER
MPN / Reference	P3-63/I3/SVB/N/HI11
Catalog number	Y7-207342
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-2D50D81C3A
Generated	2026-08-06

Product Overview

Main switch, +housing, 3p+N+1N/O+1N/C, 63A, handle red yellow, lockable

P3-63/I3/SVB/N/HI11

Eaton Moeller® series P3 On-Off switch, P3, 63 A, surface mounting, 3 pole + N, 1 N/O, 1 N/C, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) position

Main switch/switch-disconnector on-off according to IEC/EN 60947-3, 690V/63A, degree of protection Front IP65, handle red with yellow locking collar lockable with 3 padlocks, switch-disconnectors P3 have a very compact and robust design. The manual drive act directly to the connection of the contacts. The contacts are forced open when switching off. Design general: insulating material-surface mounting enclosure, flush mounting, rear mounting, IVS service distribution board mounting

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series P3 Main switch Catalog Number 207342 Model Code P3-63/I3/SVB/N/HI11 EAN 4015082073428 Product Length/Depth 160 mm Product Height 222 mm Product Width 120 mm Product Weight 1.118 kg

Compliances CE

ETIM for 207342 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)
Yes
Version as maintenance-/service switch (EF006986)
Yes
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
Yes
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Max. rated operation voltage U_e AC (EF007355)
690 V
Rated operating voltage (EF001435)
690 V
Rated permanent current I_u (EF001389)
63 A
Rated permanent current at AC-23, 400 V (EF011777)
63 A
Rated permanent current at AC-21, 400 V (EF009165)
63 A
Rated operation power at AC-3, 400 V (EF001364)
30 kW
Rated short-time withstand current I_{cw} (EF007050)
1.26 kA
Rated operation power at AC-23, 400 V (EF007027)
37 kW
Switching power at 400 V (EF009166)
30 kW
Conditioned rated short-circuit current I_q (EF001444)
100 kA
Number of poles (EF001391)
4
Number of auxiliary contacts as normally closed contact (EF001377)
1
Number of auxiliary contacts as normally open contact (EF001376)
1
Number of auxiliary contacts as change-over contact (EF003531)
0
Motor drive optional (EF007386)
No
Motor drive integrated (EF006697)
No
Voltage release optional (EF007491)
No
Device construction (EF008...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P3-63/I3/SVB/N/HI11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.