

INDUSTRIAL COMPONENT DATA

P3-63/I4-RT-NA 255899 Y7-255899 EATON ELECTRIC On-Off switch, P3, 63 A, surface mounting, 3 pole, Emergency ..

Brand: EATON - MOELLER | Manufacturer Part Number: P3-63/I4-RT-NA



Manufacturer	EATON - MOELLER
MPN / Reference	P3-63/I4-RT-NA
Catalog number	Y7-255899
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-903B525D67
Generated	2026-08-06

Product Overview

On-Off switch, P3, 63 A, surface mounting, 3 pole, Emergency switching off function, with red thumb grip and yellow front plate, UL/CSA

P3-63/I4-RT-NA

On-Off switch, Product range: On-Off switch, Part group reference: P3, Stop Function: Emergency switching off function, with red thumb grip and yellow front plate, Notes: UL/CSA, Information about equipment supplied: Auxiliary contact or neutral conductor fitted by user., 3 pole, Degree of Protection: IP65, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series P3 On-off switch Catalog Number 255899 Model Code P3-63/I4-RT-NA EAN 4015082558994 Product Length/Depth 124 mm Product Height 240 mm Product Width 160 mm Product Weight 1.002 kg

Certifications CSA

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60204

CSA Class No.: 3211-05

UL File No.: E36332

CSA-C22.2 No. 94

IEC/EN 60947-3

UL Category Control No.: NLRV

VDE 0660

UL 60947-4-1

CE

CSA File No.: 012528

IEC/EN 60947

UL

ETIM for 255899 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

Yes

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated operating voltage (EF001435)

690 V

Rated permanent current Iu (EF001389)

63 A

Rated permanent current at AC-23, 400 V (EF011777)

63 A

Rated permanent current at AC-21, 400 V (EF009165)

63 A

Rated operation power at AC-3, 400 V (EF001364)

30 kW

Rated short-time withstand current Icw (EF007050)

1.26 kA

Rated operation power at AC-23, 400 V (EF007027)

30 kW

Switching power at 400 V (EF009166)

30 kW

Conditioned rated short-circuit current Iq (EF001444)

100 kA

Number of poles (EF001391)

3

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P3-63/I4-RT-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.