

INDUSTRIAL COMPONENT DATA

P3-63/ST/SVB-SW 201716 EATON ELECTRIC Main switch, +steel enclosure, 3p, 63A, handle black, lockable

Brand: EATON - MOELLER | Manufacturer Part Number: P3-63/ST/SVB-SW



Manufacturer	EATON - MOELLER
MPN / Reference	P3-63/ST/SVB-SW
Catalog number	201716
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-11227E3650
Generated	2026-08-04

Product Overview

Main switch, +steel enclosure, 3p, 63A, handle black, lockable

General switch; 3-pole; 63; Mount steel case; Lever Black; Lockable in the 0 position (OFF)

Main switch/switch-disconnector on-off according to IEC/EN 60947-3, 690V/63A, steel sheet enclosure, degree of protection Front IP55, handle black with black locking collar lockable with 3 padlocks, switch-disconnectors P3 have a very compact and robust design. The manual drive act directly to the connection of the contacts. The contacts are forced open when switching off. Design general: insulating material-surface mounting enclosure, flush mounting, rear mounting, IVS service distribution board mounting

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Main switch, +steel enclosure, 3p, 63A, handle black, lockableMain switch/switch-disconnector on-off according to IEC/EN 60947-3, 690V/63A, steel sheet enclosure, degree of protection Front IP55, handle black with black locking collar lockable with 3 padlocks, switch-disconnectors P3 have a very compact and robust design. The manual drive act directly to the connection of the contacts. The contacts are forced open when switching off. Design general: insulating material-surface mounting enclosure, flush mounting, rear mounting, IVS service distribution board mountingTechnical data ETIM 4.0

Version as switch disconnecter compactYesVersion as main switchYesVersion as maintenance-/service switchYesVersion as safety switchNoVersion as emergency stop installationNoMax. rated operation voltage Ue AC690 VRated permanent current Iu63 ARated operation power AC-3, 400 V30 kWRated operation power at AC-23, 400V37 kWConditioned rated short-circuit current Iq0 kANumber of poles3Number of auxiliary contacts as normally closed contact0Number of auxiliary

contacts as normally open contact0Number of auxiliary contacts as change-over contact0Motor drive optionalNoMotor drive integratedNoVoltage release optionalNoDevice constructionBuilt-in device fixed built-in techniqueSuitable for ground mountingNoSuitable for front mountingNoSuitable for front mounting centerNoSuitable for distribution board installationNoSuitable for intermediate mountingNoType of control element-InterlockableYesConnection...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P3-63/ST/SVB-SW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.