

INDUSTRIAL COMPONENT DATA

FAK-R/V/KC01/IY 229747 Y7-229747 EATON ELECTRIC Palm switch, 1 N/C, emergency switching off, surface mounting

Brand: EATON - MOELLER | Manufacturer Part Number: FAK-R/V/KC01/IY



Manufacturer	EATON - MOELLER
MPN / Reference	FAK-R/V/KC01/IY
Catalog number	Y7-229747
Category	Foot-/palm switch complete
Minimum order	1 Pcs
Document ID	EO-4DCA79CD86
Generated	2026-08-05

Product Overview

Palm switch, 1 N/C, emergency switching off, surface mounting

FAK-R/V/KC01/IY

Foot and palm switch, Complete unit, Function: maintained, Description: Pull to release, Emergency stop pushbutton tamper-proof to ISO 13850/EN 418, Contacts N/C = Normally closed: 1 NC, Contacts Notes = safety function, by positive opening to IEC/EN 60947-5-1, Color Button: Red, Color enclosure top: Yellow, Color Enclosure base: Black, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-5, VDE 0660, Degree of protection, IEC/EN 60529: IP66, IP67, IP69K, Mounting position: As required

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Palm switch, 1 N/C, emergency switching off, surface mountingFoot and palm switch, Complete unit, Function: maintained, Description: Pull to release, Emergency stop pushbutton tamper-proof to ISO 13850/EN 418, Contacts N/C = Normally closed: 1 NC, Contacts Notes = safety function, by positive opening to IEC/EN 60947-5-1, Color Button: Red, Color enclosure top: Yellow, Color Enclosure base: Black, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-5, VDE 0660, Degree of protection, IEC/EN 60529: IP66, IP67, IP69K, Mounting position: As required

General specificationsProduct nameEaton Moeller® series FAK Palm switchPart

no.FAK-R/V/KC01/IYEAN4015082297473Product Length/Depth100 millimetreProduct height85 millimetreProduct width85 millimetreProduct weight0.308 kilogramCertificationsUL 508
IEC/EN 60947-5

UL
CSA-C22.2 No. 94-91
CSA Class No.: 3211-03
UL File No.: E29184
CSA
CSA-C22.2 No. 14-05
IEC/EN 60947-5-5
UL Category Control No.: NKCR
CE
CSA File No.: 012528
VDE 0660Product TradenameFAKProduct TypePalm switchProduct Sub TypeNoneCatalog NotesContacts with safety function, by positive opening to IEC/EN 60947-5-1Features & FunctionsEnclosure colorYellow
BlackFeaturesTamper-proof (according to ISO 13850/EN 418)
Emergency stop pushbuttonUnlocking methodPull-releaseGeneral informationConnection to SmartWire-DTNoDegree of protectionNEMA 12
IP67/IP69KLifespan, mechanical100,000 OperationsMounting positionAs requiredOpening diameter0 mmOperating frequency600 Operations/hProduct...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAK-R/V/KC01/IY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.