

INDUSTRIAL COMPONENT DATA

FAK-S/KC10/I 115963 Y7-115963 EATON ELECTRIC EVC-S-32S2R2120 EV Charging Station S series

Brand: EATON - MOELLER | Manufacturer Part Number: FAK-S/KC10/I



Manufacturer	EATON - MOELLER
MPN / Reference	FAK-S/KC10/I
Catalog number	Y7-115963
Category	Foot-/palm switch complete
Minimum order	1 Pcs
Document ID	EO-81084F9926
Generated	2026-08-06

Product Overview

EVC-S-32S2R2120 EV Charging Station S series

FAK-S/KC10/I

Eaton Moeller® series FAK Palm switch, 1N/O, mushroom black

Foot and palm switch, Connection to SmartWire-DT: no, Degree of protection, IEC/EN 60529: IP66, IP67, IP69K, Mounting position: As required

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series FAK Palm switch Catalog Number 115963 Model Code FAK-S/KC10/I EAN

4015081157037 Product Length/Depth 100 mm Product Height 85 mm Product Width 85 mm Product Weight 0.35 kg

Certifications IEC/EN 60947-5-5

VDE 0660 Features & Functions

Enclosure color Black

Gray Unlocking method None General

Connection to SmartWire-DT No Degree of protection NEMA 4X

IP67/IP69K Lifespan, mechanical 1,000,000 Operations (AC operated) Mounting position As required Opening diameter 0 mm Operating frequency 3600 Operations/h Product category Foot and palm switches Shock resistance Mechanical, According to IEC/EN 60068-2-27

15 g, Mechanical, According to IEC/EN 60068-2-27, Half-Sinusoidal shock 11 ms Type Basic device Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Actuator

Actuating force 40 N Actuator color Black Actuator function Spring-return

Momentary Contacts

Number of contacts (normally closed contacts) 0 Number of contacts (normally open contacts) 1 Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0.11 W Rated operational current for specified heat dissipation (I_n) 6 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the pr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAK-S/KC10/I with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.