

INDUSTRIAL COMPONENT DATA

P1-32/I2/SVA(S)-RT 207327 Y7-207327 EATON ELECTRIC Panic switches, 3 pole, 32 A, Cylinder lock SVA, front pl..

Brand: EATON - MOELLER | Manufacturer Part Number: P1-32/I2/SVA(S)-RT



Manufacturer	EATON - MOELLER
MPN / Reference	P1-32/I2/SVA(S)-RT
Catalog number	Y7-207327
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-1EAB0645B6
Generated	2026-08-05

Product Overview

Panic switches, 3 pole, 32 A, Cylinder lock SVA, front plate 0-1, 90 °, maintained, surface mounting, P

P1-32/I2/SVA(S)-RT

Eaton Moeller® series P1 Panic switches, P1, 32 A, surface mounting, 3 pole, with red thumb grip and yellow front plate, Cylinder lock SVA

Panic switch, Product range: Switch with locking mechanism, Part group reference: P1, Stop Function: Emergency switching off function, with red thumb grip and yellow front plate, Information about equipment supplied: Auxiliary contact or neutral conductor fitted by user., with two keys, 3 pole, locking arrangement: Cylinder lock SVA, Notes: If the key is withdrawn in position 1 the switch can be switched off but not on again without the key., Degree of Protection: IP65, Design: surface mounting, Switching angle: 90 °, Switching performance: maintained, front plate: 0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW , Rated uninterrupted current: Iu = 32 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 Panic switch Catalog Number 207327 Model Code P1-32/I2/SVA(S)-RT EAN 4015082073275 Product Length/Depth 126 mm Product Height 180 mm Product Width 100 mm Product Weight 0.544 kg
Certifications VDE 0660
IEC/EN 60204

IEC/EN 60947

IEC/EN 60947-3

ETIM for 207327 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

No

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated operating voltage (EF001435)

690 V

Rated permanent current Iu (EF001389)

32 A

Rated permanent current at AC-23, 400 V (EF011777)

32 A

Rated permanent current at AC-21, 400 V (EF009165)

32 A

Rated operation power at AC-3, 400 V (EF001364)

13 kW

Rated short-time withstand current Icw (EF007050)

0.64 kA

Rated operation power at AC-23, 400 V (EF007027)

15 kW

Switching power at 400 V (EF009166)

15 kW

Conditioned rated short-circuit current Iq (EF001444)

80 kA

Number of poles (EF001391)

3

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Motor drive optional (EF007386)

No

Motor drive integrated (EF006697)

No

Voltage release opt...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-32/I2/SVA(S)-RT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.