

INDUSTRIAL COMPONENT DATA

T0-2-1/I1/SVA(S) 207084 Y7-207084 EATON ELECTRIC Panic switches, 3 pole, 20 A, Cylinder lock SVA, front plat..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-1/I1/SVA(S)



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-1/I1/SVA(S)
Catalog number	Y7-207084
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-E1A492235D
Generated	2026-08-06

Product Overview

Panic switches, 3 pole, 20 A, Cylinder lock SVA, front plate 0-1, 90 °, maintained, surface mounting, P T0-2-1/I1/SVA(S)

Eaton Moeller® series T0 Panic switches, T0, 20 A, surface mounting, 3 pole, with black thumb grip and front plate, Cylinder lock SVA

Panic switch, Product range: Switch with locking mechanism, Part group reference: T0, with black thumb grip and front plate, Information about equipment supplied: with two keys, 3 pole, locking arrangement: Cylinder lock SVA, Notes: If the key is withdrawn in position 1 the switch can be switched off but not on again without the key., Locking facility: Lockable in position 0 with cover interlock, Degree of Protection: IP65, Design: surface mounting, Switching angle: 90 °, Switching performance: maintained, front plate: 0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 2 contact unit(s) , Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Panic switch Catalog Number 207084 Model Code T0-2-1/I1/SVA(S) EAN 4015082070847 Product Length/Depth 137 mm Product Height 102 mm Product Width 80 mm Product Weight 0.396 kg Certifications IEC/EN 60947 VDE 0660

IEC/EN 60204

IEC/EN 60947-3

ETIM for 207084 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

No

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated operating voltage (EF001435)

690 V

Rated permanent current Iu (EF001389)

20 A

Rated permanent current at AC-23, 400 V (EF011777)

13.3 A

Rated permanent current at AC-21, 400 V (EF009165)

20 A

Rated operation power at AC-3, 400 V (EF001364)

5.5 kW

Rated short-time withstand current Icw (EF007050)

0.32 kA

Rated operation power at AC-23, 400 V (EF007027)

5.5 kW

Switching power at 400 V (EF009166)

5.5 kW

Conditioned rated short-circuit current Iq (EF001444)

6 kA

Number of poles (EF001391)

3

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Motor drive optional (EF007386)

No

Motor drive integrated (EF006697)

No

Voltage release op...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-1/I1/SVA(S) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.