


INDUSTRIAL COMPONENT DATA

DILM150-XP1 284769 Y7-284769 EATON ELECTRIC Paralleling link, DILM80 to DILM150

Brand: EATON - MOELLER | Manufacturer Part Number: DILM150-XP1



Manufacturer	EATON - MOELLER
MPN / Reference	DILM150-XP1
Catalog number	Y7-284769
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-0EB21FED49
Generated	2026-08-03

Product Overview

Paralleling link, DILM80 to DILM150

DILM150-XP1

Eaton Moeller® series DILM Paralleling link, DILM80 to DILM150

Paralleling link, Product range: Accessories, Wiring accessories, For use with: DILM80 - DILM170, DILMF80 - DILMF150

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM paralleling link Catalog Number 284769 Model Code DILM150-XP1 EAN 4015082847692 Product Length/Depth 102 mm Product Height 76 mm Product Width 83 mm Product Weight 0.957 kg

Certifications CSA File No.: 012528

UL

CSA-C22.2 No. 14-05

UL File No.: E29096

CSA Class No.: 3211-03

CE

CSA

UL 508

IEC/EN 60947-4-1

UL Category Control No.: NLDX Catalog Notes AC1 current carrying capacity of the open contactor increases by a factor of 2.5 General

Accessory/spare part type Connecting bridge Product category Accessories Protection Protected against accidental contact in accordance to VDE 0106 part 100 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Terminal capacities

Terminal capacity 1 x (35 - 300) mm², stranded

2 x (35 - 120) mm², stranded

2 x (11 x 21 x 1) mm (Number of segments x width x thickness), Flat conductor Screw size 5 mm AF, Hexagon socket-head spanner, Terminal screw, Main cables Tightening torque 14 Nm, Screw terminal Conventional thermal current

Conventional thermal current ith of main contacts (1-pole, open) 400 A Design verification

Equipment heat dissipation, current-dependent P_{vid} 37.8 W Heat dissipation capacity P_{diss} 0 W Rated operational current for specified heat dissipation (I_n) 400 A 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product sta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM150-XP1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.