


INDUSTRIAL COMPONENT DATA

DILM32-XP1 281194 Y7-281194 EATON ELECTRIC Paralleling link, for DILM1732

Brand: EATON - MOELLER | Manufacturer Part Number: DILM32-XP1



Manufacturer	EATON - MOELLER
MPN / Reference	DILM32-XP1
Catalog number	Y7-281194
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-C53BFD6324
Generated	2026-08-02

Product Overview

Paralleling link, for DILM1732

DILM32-XP1

Eaton Moeller® series DILM Paralleling link, for DILM17-32

Paralleling link, Product range: Accessories, Wiring accessories, For use with: DILM17 - DILM32, DILMF8 - DILMF32

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM paralleling link Catalog Number 281194 Model Code DILM32-XP1 EAN 4015082811945 Product Length/Depth 43 mm Product Height 42 mm Product Width 33 mm Product Weight 0.055 kg

Certifications IEC/EN 60947-4-1

CSA-C22.2 No. 14-05

UL 508

UL File No.: E29096

CSA File No.: 012528

CE

CSA Class No.: 3211-03

UL Category Control No.: NLDX

CSA

UL Catalog Notes AC1 current carrying capacity of the open contactor increases by a factor of 2.5 General
Accessory/spare part type Connecting bridge Product category Accessories Protection Protected against accidental contact
in accordance to VDE 0106 part 100 Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Terminal capacities
Terminal capacity 1 x (16 - 50) mm²
1 x (16 - 35) mm²
16 mm², solid Screwdriver size 2, Terminal screw, Pozidriv screwdriver Tightening torque 4 Nm, Screw terminal Short-circuit
rating
Short-circuit current rating (basic rating) 5 kA, SCCR (UL/CSA)
125 A, max. Fuse, SCCR (UL/CSA)
125 A, max. CB, SCCR (UL/CSA) Short-circuit current rating (high fault at 480 V) 10/100 kA, Fuse, SCCR (UL/CSA)
10/65 kA, CB, SCCR (UL/CSA)
50/32 A, max. CB, SCCR (UL/CSA)
125/70 A, Class J, max. Fuse, SCCR (UL/CSA) Short-circuit current rating (high fault at 600 V) 10/22 kA, CB, SCCR
(UL/CSA)
125/125 A, Class J, max. Fuse, SCCR (UL/CSA)
10/100 kA, Fuse, SCCR (UL/CSA)
50/32 A, max. CB, SCCR (UL/CSA) Conventional thermal...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM32-XP1 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.