


INDUSTRIAL COMPONENT DATA

DILM185-XP1 208292 Y7-208292 EATON ELECTRIC Paralleling link, for DILM185, (2 off)

Brand: EATON - MOELLER | Manufacturer Part Number: DILM185-XP1



Manufacturer	EATON - MOELLER
MPN / Reference	DILM185-XP1
Catalog number	Y7-208292
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-890E9CFF2C
Generated	2026-08-04

Product Overview

Paralleling link, for DILM185, (2 off)

DILM185-XP1

Eaton Moeller® series DILM Paralleling link, for DILM185, (2 off)

Paralleling link, Product range: Accessories, Wiring accessories, For use with: DILM185A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors more than 170 A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM paralleling link Catalog Number 208292 Model Code DILM185-XP1 EAN 4015082082925 Product Length/Depth 60 mm Product Height 80 mm Product Width 120 mm Product Weight 1.45 kg

Compliances CE Catalog Notes AC1 current carrying capacity of the open contactor increases by a factor of 2.5 General

Accessory/spare part type Connecting bridge Fitted with: Cover for busbar tag shroud Product category Accessories

Protection Protected against accidental contact in accordance to VDE 0106 part 100 Climatic environmental conditions

Ambient operating temperature - min -40 °C Ambient operating temperature - max 60 °C Terminal capacities

Terminal capacity 2 x (0.75 - 2.5) mm², flexible with ferrule

2 x (0.75 - 4) mm², solid, Control circuit cables

2 x (20 x 32 x 0.5) mm (Number of segments x width x thickness), Flat conductor

1 x (0.75 - 2.5) mm², flexible with ferrule

2 x (11 x 21 x 1) mm (Number of segments x width x thickness), Flat conductor

1 x (0.75 - 4) mm², solid

1 x (6 x 16 x 0.8) mm (Number of segments x width x thickness), Flat conductor Screw size 5 mm AF, Hexagon

socket-head spanner, Terminal screw Tightening torque 6 Nm, Screw terminal Conventional thermal current I_{th}

Conventional thermal current I_{th} of main contacts (1-pole, open) 700 A Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM185-XP1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.