

INDUSTRIAL COMPONENT DATA

DILM65-XP1 281195 Y7-281195 EATON ELECTRIC Paralleling link, for DILM4065

Brand: EATON - MOELLER | Manufacturer Part Number: DILM65-XP1



Manufacturer	EATON - MOELLER
MPN / Reference	DILM65-XP1
Catalog number	Y7-281195
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-41C0299A55
Generated	2026-08-02

Product Overview

Paralleling link, for DILM4065

DILM65-XP1

Eaton Moeller® series DILM Paralleling link, for DILM40-65

Paralleling link, Product range: Accessories, Wiring accessories, For use with: DILM40 - DILM72, DILMF40 - DILMF65

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM paralleling link Catalog Number 281195 Model Code DILM65-XP1 EAN 4015082811952 Product Length/Depth 77 mm Product Height 53 mm Product Width 47 mm Product Weight 0.24 kg

Certifications CSA File No.: 012528

UL 508

UL File No.: E29096

IEC/EN 60947-4-1

UL

UL Category Control No.: NLDX

CE

CSA Class No.: 3211-03

CSA-C22.2 No. 14-05

CSA Catalog Notes AC1 current carrying capacity of the open contactor increases by a factor of 2.5 General
Accessory/spare part type Connecting bridge Product category Accessories Protection Protected against accidental contact
in accordance to VDE 0106 part 100 Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Terminal capacities
Terminal capacity 1 x (16 - 120) mm², stranded, Main cables
1 x (16 - 120) mm², flexible with ferrule, Main cables
16 mm², solid Screw size 5 mm AF, Hexagon socket-head spanner, Terminal screw Tightening torque 14 Nm, Screw
terminal Conventional thermal current
Conventional thermal current Ith of main contacts (1-pole, open) 180 A Design verification
Equipment heat dissipation, current-dependent Pvid 1.5 W Heat dissipation capacity Pdis 0 W Rated operational current
for specified heat dissipation (In) 215 A 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1
Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verificatio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM65-XP1 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.