


INDUSTRIAL COMPONENT DATA

DILM12-XP1 281193 Y7-281193 EATON ELECTRIC Paralleling link, for DILM712 / MP20

Brand: EATON - MOELLER | Manufacturer Part Number: DILM12-XP1



Manufacturer	EATON - MOELLER
MPN / Reference	DILM12-XP1
Catalog number	Y7-281193
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	5 Pcs
Document ID	EO-B8C6E7B3B5
Generated	2026-08-05

Product Overview

Paralleling link, for DILM712 / MP20

DILM12-XP1

Eaton Moeller® series DILM Paralleling link, for DILM7-12/MP20

Paralleling link, Product range: Accessories, Wiring accessories, For use with: DILM7 - DILM15, DILMP20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM paralleling link Catalog Number 281193 Model Code DILM12-XP1 EAN 4015082811938 Product Length/Depth 34 mm Product Height 30 mm Product Width 32 mm Product Weight 0.039 kg

Certifications CSA File No.: 012528

IEC/EN 60947-4-1

UL Category Control No.: NLDX

CSA

CSA-C22.2 No. 14-05

CE

UL 508

UL File No.: E29096

CSA Class No.: 3211-03

UL General

Accessory/spare part type Connecting bridge Product category Accessories Protection Protected against accidental contact in accordance to VDE 0106 part 100 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Terminal capacities

Terminal capacity 1 - 16 mm², solid

1 x (0.5 - 25) mm², stranded

2 x (0.5 - 16) mm², flexible with ferrule

6 x 9 x 0.8 mm Number of segments x width x thickness, Flat conductor

2 x (0.5 - 16) mm², stranded

1 x (0.5 - 25) mm², flexible with ferrule Screwdriver size 2, Terminal screw, Pozidriv screwdriver Tightening torque 4 Nm,

Screw terminal Conventional thermal current

Conventional thermal current I_{th} of main contacts (1-pole, open) 50 A Design verification

Equipment heat dissipation, current-dependent P_{vid} 0.2 W Heat dissipation capacity P_{diss} 0 W Rated operational current for specified heat dissipation (I_n) 50 A 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM12-XP1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.