

INDUSTRIAL COMPONENT DATA

P1DILEM 019095 Y7-19095 EATON ELECTRIC Paralleling link, main terminals, for DILEM

Brand: EATON - MOELLER | Manufacturer Part Number: P1DILEM



Manufacturer	EATON - MOELLER
MPN / Reference	P1DILEM
Catalog number	Y7-19095
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	5 Pcs
Document ID	EO-FD51DD1667
Generated	2026-08-02

Product Overview

Paralleling link, main terminals, for DILEM

Parallel Joint Set For DILEM Contactors...

Eaton Moeller® series DILEM Paralleling link, main terminals, for DILEM

Paralleling link, Paralleling link, consisting of two 4 pole paralleling links, 4th pole can be broken off, 4 pole: Ith = 60 A open, 3 pole: Ith = 50 A open, AC-1 current carrying capacity of the open contactor increases by a factor of 2.5, For use with: DILEEM, DILEM12, DILEM

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILEM Accessory Paralleling link Catalog Number 019095 Model Code P1DILEM
EAN 4015080190950 Product Length/Depth 29 mm Product Height 33 mm Product Width 33 mm Product Weight 0.039 kg
Certifications UL Category Control No.: NLDX

CSA File No.: 012528

CE

CSA

CSA Class No.: 3211-07

UL 508

CSA-C22.2 No. 14-05

UL File No.: E29096

IEC/EN 60947-4-1

UL General

Accessory/spare part type Connecting bridge Product category Accessories Protection Protected against accidental contact in accordance to VDE 0106 part 100 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 50 °C Design verification

Equipment heat dissipation, current-dependent P_{vid} 0.08 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0.03 W Rated operational current for specified heat dissipation (I_n) 50 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation Meets the product standard's requirements. 10.2.5 Liftin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1DILEM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.