

INDUSTRIAL COMPONENT DATA

PDIM-40/4 111760 Y7-111760 EATON ELECTRIC Residual current circuit-breaker, 40A, 4p, 0mA, AC-Char

Brand: EATON - MOELLER | Manufacturer Part Number: PDIM-40/4



Manufacturer	EATON - MOELLER
MPN / Reference	PDIM-40/4
Catalog number	Y7-111760
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-87F8D6408F
Generated	2026-08-04

Product Overview

Residual current circuit-breaker, 40A, 4p, 0mA, AC-Char

PDIM-40/4

Eaton Moeller series xPole - PDIM RCCB. Residual current circuit-breaker, 40A, 4p, 0mA, AC-Char

Leakage current meter PDIM, 4 pole, Rated current I_n : 40 A, Rated short-circuit strength I_{cn} : 10 kA, Rated fault current $I_{?N}$: adjustable: 0.03/0.1/0.3/0.5/1 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

General specifications

Product Name Eaton Moeller series xPole - PDIM RCCB Catalog Number 111760 Model Code PDIM-40/4 EAN

4015081113101 Product Length/Depth 80 mm Product Height 65.5 mm Product Width 70 mm Product Weight 0.334 kg

Compliances RoHS conform Certifications DIN/EN 62020 Product specifications

Used with Leakage current monitor

PDIM Type Special features Current test marks as per inscription

Maximum operating temperature is 60 °C: Starting at 40 °C, the max. permissible continuous current decreases by 2.5% for every 1 °C

Switching contact (potential-free) 10 A / 240 V~

Application Switchgear for industrial and advanced commercial applications

xEffect - Switchgear for industrial and advanced commercial applications

Amperage Rating 40 A Features Selective protection

Leakage current monitor

Additional equipment possible 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PDIM-40/4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.