

INDUSTRIAL COMPONENT DATA

PFIM-25/2/003-A-GV 139514 Y7-139514 EATON ELECTRIC

Supply MIN 30. Differential int. PFIM, 2P, 25A, 30mA, cla..

Brand: EATON - MOELLER | Manufacturer Part Number: PFIM-25/2/003-A-GV



Manufacturer	EATON - MOELLER
MPN / Reference	PFIM-25/2/003-A-GV
Catalog number	Y7-139514
Category	Residual current circuit breaker (RCCB)
Minimum order	30 Pcs
Document ID	EO-5CB479895D
Generated	2026-08-05

Product Overview

Supply MIN 30. Differential int. PFIM, 2P, 25A, 30mA, class A
Residual current circuit breaker (RCCB), 25A, 2pole, 30mA, type A, large packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Differential
--------------	---

Additional Product Information

Residual current circuit breaker (RCCB), 25A, 2pole, 30mA, type A, large packagingDelivery program
Basic functionResidual current circuit-breakersNumber of poles2 poleApplicationResidual current circuit-breaker for residential and commercial applicationsRated current [In]25 ARated short-circuit strength [Icn]10 kARated fault current [I?N]0.03 ATypeType ATrippingnon-delayed s...Product rangePFIMSensitivityPulse-current sensitiveImpulse withstand currentPartly surge-proof 250 ATechnical data
ElectricalTypes conform toIEC/EN 61008Current test marksAs per inscriptionStandardsIEC/EN 61008Rated operational voltage [Ue][Ue]Rated operating voltage [Ue]230 V ACRated frequency [f]50 HzLimit values of the operating voltageTest circuit196 - 264 V ACSensitivityPulse-current sensitiveRated insulation voltage [Ui]440 VRated impulse withstand voltage [Uimp]4 kVRated short-circuit strength [Icn]10 kAMax. admissible back-up fuseShort-circuit [gG/gL]63 AMax. admissible back-up fuseOverload [gG/gL]25 ARated making and breaking capacity / Rated residual making and breaking capacity [Im/I?m]500 AMax. back-up fuse25 A gL/gGMaximum max. as short-circuit protective deviceBack-up fuse63 A gLlifespanElectrical [Operations]? 4000lifespanMechanical [Operations]? 20000ReferencesAuxiliary switch for subsequent installationZ-HK 248432Tripping signal contact for subsequent installationZ-NHK 248434Remote control and automatic switching deviceZ-FW/LP 248296Compact enclosureKLV-TC-2 276240Sealing cover setZ-RC/...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PFIM-25/2/003-A-GV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.