

INDUSTRIAL COMPONENT DATA

EMR5-A400-1 134222 EATON ELECTRIC Phase imbalance monitoring relay, 2W, 300-500V/50/60Hz, tv 0.1-30s

Brand: EATON - MOELLER | Manufacturer Part Number: EMR5-A400-1



Manufacturer	EATON - MOELLER
MPN / Reference	EMR5-A400-1
Catalog number	134222
Category	Phase monitoring relay
Minimum order	1 Pcs
Document ID	EO-CE56769059
Generated	2026-08-06

Product Overview

Phase imbalance monitoring relay, 2W, 300-500V/50/60Hz, tv=0.1-30s

Relay for monitoring phase imbalance; 2 W; 300-500V/50/60 Hz; tv=0.1-30 s

Phase imbalance monitoring relay EMR5-A... according to IEC/EN 60255-6, 22.5 mm wide, 300-500VAC, phase Sequence, phase failure, imbalance (adjustable threshold values 2-25%), response delay: none or adjustable from 0.1 to 30 s

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Relay timers (KETR, KEMR, KESR)
--------------	---

Additional Product Information

Fuse-link, low voltage, 1.5 A, AC 250 V, 10 x 38 mm, supplemental, UL, CSA, time-delay Fuse, Fuse-link, low voltage, 1.5 A, AC 250 V, 10 x 38 mm, supplemental, UL, CSA, time-delay, cylindrical, colour-coded, green, general purpose, lighting circuits, meter circuits, UL 248-14, melamine tube [Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 1.5 A Rated voltage AC 250 V

Size 10 x 38 mm Utilization category supplemental Description colour-coded

green usable for size/applications general purpose, lighting circuits, meter circuits Release characteristic [class] time-delay

Standard/Approval UL

CSA Shape cylindrical Material melamine tube Standards/Regulations UL 248-14 , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) ()

[AFZ797013]) Size 10x38 mm Rated voltage 250 - 250 V Rated voltage Other Voltage type AC Utilization category Other Rated operating frequency 45 - 62 Hz Nominal current 1.5 A With striker No Release characteristic M (Midget) Breaking

capacity 0.1 kA]

ETIM for 134222 Relays (EC001441)

Feature Name

Feature Value

Type of electric connection (EF003961)

Screw connection

With detachable clamps (EF003340)

No

External power supply required (EF003292)

No

Phase sequence monitoring (EF003412)

Yes

Phase f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EMR5-A400-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.