

INDUSTRIAL COMPONENT DATA

EMR4-F500-2 221784 EATON ELECTRIC Phase sequence relay, 3p, 2W, 200-500VAC

Brand: EATON - MOELLER | Manufacturer Part Number: EMR4-F500-2



Manufacturer	EATON - MOELLER
MPN / Reference	EMR4-F500-2
Catalog number	221784
Category	Phase monitoring relay
Minimum order	1 Pcs
Document ID	EO-D1A704C405
Generated	2026-08-05

Product Overview

Phase sequence relay, 3p, 2W, 200-500VAC

Phase sequence relay; 3 poles; 2 W; 200-500 V AC

Phase sequence relay for monitoring of three-phase systems for phase sequence and phase failure $< 0.6 \times U_e$, supply voltage by mains voltage 200-500V AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Relay timers (KETR, KEMR, KESR)
--------------	---

Additional Product Information

Phase sequence relay, 3p, 2W, 200-500VAC Alternate Catalog No. EMR4-F500-2 EL-Nummer (Norway) 4133314 Phase sequence relay for monitoring of three-phase systems for phase sequence and phase failure $< 0.6 \times U_e$, supply voltage by mains voltage 200-500V AC [Delivery program

This item will continue to be available for a limited time only and is being replaced by the following item: 184789, EMR4-F500-2 Product range EMR Measuring and monitoring relays Basic function Phase sequence relays Monitoring of three-phase networks

Phase failure detection at $< 0.6 \times U_e$

Power supply from the measuring circuit Monitoring voltage per phase [UN] 200 - 500 V AC, 50/60 Hz V AC Monitoring of Phase sequence

Phase failure Contact sequence Supply voltage 200 - 500 V AC, 50/60 Hz , Technical data

Technical data in sheet catalogue Other technical data (sheet catalogue) Phase sequence relays , Design verification as per IEC/EN 61439

Technical data for design verification Rated operational current for specified heat dissipation [In] 0 A Heat dissipation per pole, current-dependent [Pvid] 0 W Equipment heat dissipation, current-dependent [Pvid] 0 W Static heat dissipation, non-current-dependent [Pvs] 2 W Heat dissipation capacity [Pdiss] 0 W Operating ambient temperature min. -20 °C Operating ambient temperature max. +60 °C IEC/EN 61439 design verification 10.2 Strength of materials and parts10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.3.1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EMR4-F500-2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.