

INDUSTRIAL COMPONENT DATA

SPPT2PA-1000-2+1PE-AX 132665 EATON ELECTRIC Plug-in surge arrester with auxiliary contact, 1000 V DC, 2+Npol..

Brand: EATON - MOELLER | Manufacturer Part Number: SPPT2PA-1000-2+1PE-AX



Manufacturer	EATON - MOELLER
MPN / Reference	SPPT2PA-1000-2+1PE-AX
Catalog number	132665
Category	Surge protection device for power supply systems
Minimum order	1 Pcs
Document ID	EO-D3C88602F1
Generated	2026-08-04

Product Overview

Plug-in surge arrester with auxiliary contact, 1000 V DC, 2+Npole, non-earthed

Test class II according to IEC 61643-1, SPD part no. T2 according to EN 61643-11, part no. SPPT2PA-...-AX: version with auxiliary contact for remote messages defective SPD insert

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Delivery program Product range DC overvoltage protection

Products Surge arresters

Application field Residential buildings

Utility buildings

Open areas

Description pluggable

With auxiliary contact

Connection For ungrounded systems

Maximum uninterrupted voltage U_c V 1000

Technical data ETIM 7.0 Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941)

Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Surge protection device for power supply systems ( [ACN278011])

System configuration DC No
System configuration IT Yes
System configuration TN No
System configuration TN-C No
System configuration TN-C-S No
System configuration TN-S No
System configuration TT No
System configuration other No
Number of conductors (without earthing)
Nominal discharge surge current (8/20) kA 15
Nominal voltage AC V 0
Nominal voltage DC V 1000
Short-circuit breaking capacity (I_{sc}) kA
Max. continuous voltage AC V 0
Max. discharge surge current (8/20) kA
Max. continuous voltage DC V 1000
Mounting method DIN rail (top hat rail) 35 mm
Construction size 3 modular spacing
Max. PV-voltage V 1050
Voltage protection level kV 5
Max. conductor cross section solid (solid, stranded) mm² 25
Max. conductor cross section flexible (fine-strand) mm² 35
Voltage protection level L-N kV 0
Voltage protection level N-PE kV 0
With remote si...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SPPT2PA-1000-2+1PE-AX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.