

INDUSTRIAL COMPONENT DATA

PKDM-40/1N/C/03-A 248798 EATON ELECTRIC RCD/MCB, 40A, 300mA, miniature circuit-breaker trip curve C, 1pole+N..

Brand: EATON - MOELLER | Manufacturer Part Number: PKDM-40/1N/C/03-A



Manufacturer	EATON - MOELLER
MPN / Reference	PKDM-40/1N/C/03-A
Catalog number	248798
Category	Earth leakage circuit breaker
Minimum order	1 Pcs
Document ID	EO-BBCEE4AFBF
Generated	2026-08-04

Product Overview

RCD/MCB, 40A, 300mA, miniature circuit-breaker trip curve C, 1pole+N, residual current circuit-breaker trip characteristic: A Int. Combined, 40A, 300mA, C-curve, 1P+N, Class A

RCBO (residual-current circuit breaker with overload protection) PKDM, 1 pole+N, Tripping characteristic: C, Rated current In: 40 A, Rated switching capacity according to IEC/EN 61009: 10 kA, Rated fault current I_N: 0.3 A, Pulse-current sensitive, Partly surge-proof 250 A, Switchgear for residential and commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Tertiary and Differential

Additional Product Information

RCD/MCB, 40A, 300mA, miniature circuit-breaker trip curve C, 1pole+N, residual current circuit-breaker trip characteristic: ARCBO (residual-current circuit breaker with overload protection) PKDM, 1 pole+N, Tripping characteristic: C, Rated current In: 40 A, Rated switching capacity according to IEC/EN 61009: 10 kA, Rated fault current I_N: 0.3 A, Pulse-current sensitive, Partly surge-proof 250 A, Switchgear for residential and commercial applications

Delivery program
Basic function Combined RCD/MCB devices
Number of poles 1 pole+N
Tripping characteristic C
Application Switchgear for residential and commercial applications
Rated current [In] 40 A
Rated switching capacity according to IEC/EN 61009 10 kA
Rated fault current [I_N] 0.3 A
Type Type A
Tripping non-delayed s...
Product range PKDM
Sensitivity Pulse-current sensitive
Impulse withstand current Partly surge-proof 250 A
Technical data

Electrical Sensitivity Pulse-current sensitive Design verification as per IEC/EN 61439

Rated operational current for specified heat dissipation [In] 40 A Heat dissipation per pole, current-dependent [P_{vid}] 0 W

Equipment heat dissipation, current-dependent [P_{vid}] 8.2 W Static heat dissipation, non-current-dependent [P_{vs}] 0 W Heat

dissipation capacity [P_{diss}]₀ W Operating ambient temperature min. -25 °C Operating ambient temperature max. +40 °C Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Earth leakage circuit breaker (EC000905) Electric engineering, automation, process control engineering / Electrical installation,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKDM-40/1N/C/03-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.