

INDUSTRIAL COMPONENT DATA

PKDM-6/1N/B/03-A 248774 EATON ELECTRIC RCD/MCB, 6A, 300mA, miniature circuit-breaker trip curve B, 1pole+N, ..

Brand: EATON - MOELLER | Manufacturer Part Number: PKDM-6/1N/B/03-A



Manufacturer	EATON - MOELLER
MPN / Reference	PKDM-6/1N/B/03-A
Catalog number	248774
Category	Earth leakage circuit breaker
Minimum order	1 Pcs
Document ID	EO-6DAD7A0224
Generated	2026-08-05

Product Overview

RCD/MCB, 6A, 300mA, miniature circuit-breaker trip curve B, 1pole+N, residual current circuit-breaker trip characteristic: A Int. Combined, 6A, 300mA, B-curve, 1P+N, Class A

RCBO (residual-current circuit breaker with overload protection) PKDM, 1 pole+N, Tripping characteristic: B, Rated current In: 6 A, Rated switching capacity according to IEC/EN 61009: 10 kA, Rated fault current I_N: 0.3 A, Pulse-current sensitive, Partly surge-proof 250 A, Switchgear for residential and commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Tertiary and Differential
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller series RCBO - Residual-current circuit breaker with overcurrent protection Catalog Number 248774 Model Code PKDM-6/1N/B/03-A EAN 4015082487744 Product Length/Depth 80 mm Product Height 60 mm Product Width 35 mm Product Weight 0.225 kg Compliances CE Marked Certifications CE Product specifications Type RCBO Voltage rating 230 V Surge current capacity 0.25 kA Voltage type AC Width in number of modular spacings 2 Features Concurrently switching N-neutral Product range PKDM Rated current 6 A Rated operational current for specified heat dissipation (In) 6 A Rated switching capacity (IEC/EN 61009) 10 kA Static heat dissipation, non-current-dependent 0 W Tripping characteristic B Built-in depth 69.5 mm Current limiting class 3 Rated short-circuit breaking capacity (EN 60947-2) 0 kA Fault current rating 0.3 A Heat dissipation capacity 0 W Heat dissipation per pole, current-dependent 0 W Number of poles (protected) 1 Number of poles (total) 2 Rated switching capacity 10 kA Basic function Combined RCD/MCB devices Equipment heat dissipation, current-dependent 1.7 W Degree of protection IP20 Tripping Non-delayed Overvoltage

category III Pollution degree 2 Impulse withstand current Partly surge-proof, 250 A Leakage current type A Release characteristic B Sensitivity type Type A, pulse-current sensitive Frequency rating 50 Hz Number of poles Single-pole + N ETIM for 248774 Circuit breakers and fuses (EC000905)

Feature Name

Feature Value

Nu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKDM-6/1N/B/03-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.