

INDUSTRIAL COMPONENT DATA

PKE-COM-RTU 199344 EATON ELECTRIC Function element for connecting interface to Modbus RTU

Brand: EATON - MOELLER | Manufacturer Part Number: PKE-COM-RTU



Manufacturer	EATON - MOELLER
MPN / Reference	PKE-COM-RTU
Catalog number	Y7-199344
Category	Fieldbus, decentr. periphery - communication module
Minimum order	1 Pcs
Document ID	EO-B1C615990C
Generated	2026-07-28

Product Overview

Function element for connecting interface to Modbus RTU

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers PKZ**

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKE Function element Catalog Number 199344 Model Code PKE-COM-RTU EAN 4015081975921 Product Length/Depth 75 mm Product Height 65 mm Product Width 67.5 mm Product Weight 0.032 kg Certifications CSA File No.: 165628

IEC/EN 61131-2

UL File No.: E36332

UL Category Control No.: NKCR Catalog Notes Messages: Display of All phase currents in % - Display of Contactor state PKE - Display of Part no. of trip block - Display of Set short-circuit release value - Display of Set value of overload releases - Display of Thermal load as a % - Display of Trip indications (Overload, Short-circuit,...) - Commands: Remote disconnection of motor-protective circuit-breaker Features & Functions

Fitted with: Potential separation General

Degree of protection IP20 Explosion safety category for dust None Explosion safety category for gas None Overvoltage category II Pollution degree 2 Protocol MODBUS Type Modbus RTU PKE module Used with Brightlayer Voltage type DC Ambient conditions, mechanical

Constant acceleration 1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations Constant amplitude 3,5 mm, 5 - 8.4 Hz,

according to IEC/EN 61131-2, Vibrations Drop and topple 50 mm Drop height, Drop to IEC/EN 60068-2-31 Height of fall (IEC/EN 60068-2-32) - max 0.3 m Mounting position As PKE12/35/65 Shock resistance 15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts Climatic environmental conditions
Ambient operating t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKE-COM-RTU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.