

INDUSTRIAL COMPONENT DATA

PKE-SWD-CP 172735 Y7-172735 EATON ELECTRIC Function element for connecting interface to SmartWire-DT

Brand: EATON - MOELLER | Manufacturer Part Number: PKE-SWD-CP



Manufacturer	EATON - MOELLER
MPN / Reference	PKE-SWD-CP
Catalog number	Y7-172735
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-8EC7D108CB
Generated	2026-08-04

Product Overview

Function element for connecting interface to SmartWire-DT

PKE-SWD-CP

Eaton Moeller® series PKE Function element for connecting interface to SmartWire-DT

Function element, Connection to SmartWire-DT: yes, For use with: PKE32, PKE65

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Electronic Circuit Breakers
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKE Function element Catalog Number 172735 Model Code PKE-SWD-CP EAN 4015081692811 Product Length/Depth 75 mm Product Height 65 mm Product Width 67.5 mm Product Weight 0.028 kg

Certifications IEC/EN 61131-2 Features & Functions

Functions Remote circuit-breaker de-energization

For attachment to PKE circuit-breakers

Display of Set short-circuit release value

Display of Contactor state PKE

Display of Trip indications (Overload, Short-circuit,...)

Display of Part no. of trip block

Display of All phase currents in %

For connecting the PKE circuit-breaker with PKE-XTU(W)ACP-... trip blocks to SmartWire-DT

Display of Thermal load as a %

System protection

Display of Set value of overload releases General

Accessory/spare part type Communication and measuring function Current consumption 35 mA, SmartWire-DT network, 15-V-SWD supply Degree of protection IP20 Overvoltage category II Pollution degree 2 Product category Type Function element Ambient conditions, mechanical

Constant acceleration 1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations Constant amplitude 3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations Drop and topple 50 mm Drop height, Drop to IEC/EN 60068-2-31 Height of fall (IEC/EN 60068-2-32) - max 0.3 m Mounting position As PKE32/65 Shock resistance 15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts Climatic environmental conditions

Ambient operating temperature....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKE-SWD-CP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.